

Fire-Cryer[®] Solo - EN 54-3 Approved Voice Sounder

The EN 54-3 approved Fire-Cryer[®] Solo model FCS/C is a slimline base sounder for discreet mounting under fire detectors. It requires no special wiring and can be retrofitted to existing installations. It is fully synchronised and has an exceptionally low current consumption. The units can be used as a replacement for electronic sounders or bells to broadcast a clear message "Fire emergency. Please remain calm and evacuate the building immediately".

Features


- Sound output - 90 dB(A)
- Ultra-Slim base sounder to fit industry-standard detectors
- Omni-directional sound output
- Installer-friendly connections
- Suitable for ceiling or wall mounting
- Optional front plate for stand-alone use
- No special wiring, easily retro-fitted
- Approved to EN 54-3



Part Numbers

FCS/C: Colour - White

Installation



Specification

Operating Voltage:	20-28 V dc
Current @ 24 V dc, Peak/Avg:	27/20 mA
Effective Sound Output (Typical):	
- Alert Fast Sweep tone to BS5839	90 dB(A)*
- Voice	86 dB(A)**
Volume Adjustment from minimum output to maximum output - 18dB(A):	72 to 90 dB(A)
Weatherproofing	Internal use only
Housing Material	ABS
Temperature Range	-10 °C to +55 °C
Colour	White
Connections	Screw TB 1.5mm ²

Note:

*Tone output may vary depending on chosen sound

**Voice output may vary due to the nature of human speech

FIRE CRYER[®]
SOLO

Vimpex Limited

Star Lane, Great Wakering
Essex SS3 0PJ England
Tel: +44 (0) 1702 216999
Fax: +44 (0) 1702 216699
E-mail: sales@vimpex.co.uk
www.vimpex.co.uk



VIMPEX
Shaping Alarm Technology