#### **Product data sheet**



# FE130MD

# Eco Line double magnetic lock, 300 Kgf, monitored, surface mount

## Description

Eco Line double magnetic lock 2 x 300 kgf. Surface mounted, monitored.

### **Application**

Medium Security applications for internal or external double leaf doors.

### **Reliable Security**

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

#### Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



#### **Details**

- 2 x 300 Kgf holding power
- Monitored changeover
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Mounts easily with a minimum of tools

# FE130MD

# Eco Line double magnetic lock, 300 Kgf, monitored, surface mount

# **Technical specifications**

General	
Product type	Magnetic lock
Holding force	
Holding force kgf	300 kgf x 2
(Kilogram force)	
Holding force N (Newton	n)3000 x 2
Monitoring & statu	s
Monitored	Yes
LED indicator	Yes
Door status switch	No
Monitored changeover	Yes
Magnetic bond sensor	Yes
Electrical	
Power supply value	12 / 24 VDC
Current consumption	440 mA (+/- 2,5% @ 13,5 V) x 2
Physical	
Physical dimensions	500 x 47 x 26 mm
Colour	Aluminium

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

