

FE323-N

Magnetic lock 2430 N, Mega-LED and Relay

Mega-LED

This electromagnet is part of the new series of magnetic locks equipped with a "Mega-LED" allowing to see the LED status from a much further distance.

Security, quality and design

Security, safety and design using high quality materials, ensuring maximum strength without any residual magnetism or corrosion and proven holding force.



Details

- Strong design with high-end finish
- Corrosion proof: salt spray test (ISO 9227, ASTM B 117-90) at 35% for 96 hours
- No residual magnetism
- Built-in MOV surge protection
- L bracket and Z + L bracket set available

FE323-N

Magnetic lock 2430 N, Mega-LED and Relay

Technical specifications

General

Product type	Magnetic lock
--------------	---------------

Holding force

Holding force kgf (Kilogram force)	243
---------------------------------------	-----

Holding force N (Newton)	2430
--------------------------	------

Monitoring & status

Monitored	Yes
-----------	-----

LED indicator	Yes
---------------	-----

Door status switch	No
--------------------	----

Electrical

Operating voltage	12/24 V
-------------------	---------

Current consumption	500/250 mA
---------------------	------------

Physical

Physical dimensions	238 x 26 x 48 mm
---------------------	------------------

Net weight	~ 2 kg
------------	--------

Environmental

Operating temperature	-40° to +60°C
-----------------------	---------------

Main features

Mounting	Surface
----------	---------

Locking monitoring	Large L shaped LED for long distance status + Relay
--------------------	--

Door position monitoring	No
--------------------------	----

Corrosion Proof	Salt spray test. ISO 9227, ASTM B-117 90
-----------------	--

Residual magnetism	Guaranteed no residual magnetism
--------------------	----------------------------------

Built-in MOV Surge Protection	Yes
----------------------------------	-----

