



## FF756

UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing

### General

The FF756 is a UV / IR<sup>2</sup> flame detector in a flame proof housing. UV / IR<sup>2</sup> models have excellent response to flame while providing immunity to extraneous sources. New micro-processor technology makes the detectors independent of flame intensity enabling it to operate through smoke, a layer of oil, dust, or water vapor. A high and low sensitivity setting according to EN54-10 is provided.

### Installer and maintenance friendly

The units can be wired as conventional 2 wire, 4-20 mA, or relay contacts (fire, fault and pre alarm) in latching or non-latching operation. Remote test inputs are available to activate self-test.

A stainless steel adjustable bracket and weather shield is also available.

The units are tolerant to vibration, and wind does not affect the performance. The IR<sup>2</sup> unit has excellent tolerance to detector window contamination and can detect flame through glass windows.

A flame sensor test unit is available for accurate testing of the detectors.

### Reducing false alarms

Most IR flame sensors respond to 4.3µm light, emitted by hydrocarbon flames. By responding to 1.0 to 2.7µm light emitted by every fire, all flickering flames can be detected. Gas fires not visible to the naked eye e.g. hydrogen may also be detected.

The combination of UV and IR<sup>2</sup> detection, plus signal processing allows the UV / IR<sup>2</sup> sensor to be used without risk of false alarms in difficult situations characterised factors such as flickering blackbody radiation or arc welding.

The combination of filters and signal processing allows the sensor to be used without risk of false alarms in difficult situations characterised by factors such as flickering sunlight.



### Standard Features

- UV/Dual IR detector
- High specification units for critical applications
- IP66 Housing
- Flame proof housing
- Low current consumption
- 2 Wire, 4 - 20 mA and relay operation
- Latching and non latching operation
- High / Low sensitivity setting
- Remote self test facility
- Microprocessor controlled
- Immunity to false sources (arc welding, lightning and static)
- Conforms to EN54: Part 10

# FF756

UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing

## Specifications

Supply voltage	14 - 28 V dc
Supply current	3/9, 4/8/14, 4-20, 8-20 mA
Relay contact ratings	1 A @ 30 V dc (resistive load)
Field of view	90° min. cone
Spectral response (IR)	1.0 to 2 µm
Spectral response (UV)	185 to 260 nm
Operating temperature	-10°C to 55°C
Storage temperature	-20°C to 65°C
Relative humidity	95%; non-condensing
IP Rating	IP66
Weight	2.5 kg
IEC marking	EEx d IIC T6

## Ordering Information

Part No.	Description
FF756	UV / Dual IR flame detector in Eexd - IIC T6 flame proof housing
FF751	UV / Dual IR flame detector in die cast zinc alloy housing
FF701	UV test torch
FF703	UV/IR universal test torch
FF704	Portable Bunsen burner for flame detector testing

