

Technical Specification



Product Code: FHDV4KB4WF **Description:**



4 Channel Full HD 500GB NVR

4mm Lens 2MP 1080P Wire Free Bullet Camera - White

LINUX system	
3520V 200	
1.7kg	Ingre
	Minimun
2.4GHz	
150m (Open Field)	
4 IP cameras	(
1 x HDMI, 1 x VGA	
1 and 4	Operating
1024×768, 1280×720, 1280×1024, 1440×900, 1920×1080	Component System
	Softwa
H.264	Manua
1080P	HDMII
4ch 1080P recording	
Manual/Alarm/Motion Detection/Schedule	Mouse Remot
4ch 1080P playback	Accessories
Network/USB	F
	FH
RJ45 10M/100M	FI
HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP	FH
Web browsers, CMS, Android & iPhone apps	
1 SATA HDD, up to 4TB per HDD	
12V DC / 2A	
2	
<10W (without hard disk)	
0°C to +55°C	
257mm x 206mm x 42mm	
	3520V 200 1.7kg 2.4GHz 150m (Open Field) 4 IP cameras 1 x HDMI, 1 x VGA 1 and 4 1024 × 768, 1280 × 720, 1280 × 1024, 1440 × 900, 1920 × 1080 H.264 1080P 4ch 1080P recording Manual/Alarm/Motion Detection/Schedule 4ch 1080P playback Network/USB RJ45 10M/100M HTTP, IPV4/IPV6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP Web browsers, CMS, Android & iPhone apps 1 SATA HDD, up to 4TB per HDD 12V DC / 2A 2 <10W (without hard disk) 0°C to +55°C

Sensor Size 1/2.8" Lens 4mm Fixed Lens Resolution 1080p ess Protection IP66 Im Illumination 0.1 Lux IR Distance 20 Metres Interface RJ45 10M / 100M Ethernet Power 12V Consumption 240mA Dimensions 180mm x 65mm x 65mm Weight 575g **g Temperature** -30°C to +50°C nts Supplied m Power Supply & Power Lead are CD ıal Lead

e Control ote Control (Batteries Included)

s

FHDVC4FBWF	2MP 4mm Fixed Lens Bullet Camera in White
FHDVC4FBBWF	2MP 4mm Fixed Lens Bullet Camera in Black
FHDVC4FDWF	2MP 4mm Fixed Lens Dome Camera in White
FHDVC4FDBWF	2MP 4mm Fixed Lens Dome Camera in Black

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

