





**INNOVATIVE SOLUTIONS** 

# COR FP3 COMBINATION MANUAL CALL POINT





## SPECIFICATION

- External dimensions: width 85 mm, height 85 mm
- Surface mounted depth with back box: 55 mm
- Flush mounted depth without back box: 20 mm
- Monitoring resistors: 470 Ohm; 680 Ohm, selectable
- Blocking Diode: IN4001 (50v), selectable
- Microswitch Rating: 12A 250V
- **Standards:** EN54 11
- Activation indicator:

Window displacement Fluorescent yellow indicator in window High visibility 360° LED

- Material: Case ABS plastic
- Flush Fitting:

European Gang Pattress Standard BESA box, centres 60mm

• Cable entry: Back box 3 x 20mm (2 Top; 1 Bottom)

## **Patent Pending**

## RESETTABLE CALL POINT

The FP3 is a resettable and frangible combination EN54-11 compliant manual call point. This gives the freedom to choose whether you wish to have the convenience of a resettable call point or the false alarm deterrence of a frangible call point. The unique mechanism, designed in the United Kingdom by CQR, allows a single key to test and reset the call point after activation. It has a visible warning flag and a LED to confirm activation. The FP3, with its modern attractive design, achieves the goal of an economically priced high specification manual call point.

#### **FEATURES**

- Each box contains both resettable (plastic) and frangible (glass) windows
- When used in resettable mode, the plastic element has a positive action replicating the feel of breaking glass.
- The plastic element avoids the need to fit glass elements which can be lost or broken.
- •Snap-on front cover making it both attractive, with no visible screws, and easier to install.
- Two resistance values to ensure compatibility, and selectable with jumpers to minimise installation errors.
- •Optional clear lift up cover available for additional protection.

# **COMPARATIVE TABLE**

	FP3	OTHERS
Combined resettable & frangible windows included	•	
EN 54 compliant	•	•
Easy installation	•	
Jumpered selectable resistors	•	
360° high visibility LED	•	
Optional lift up cover	•	•



CQR Security
125 Pasture Road, Moreton, Wirral
United Kingdom, CH46 4TH
Tel: +44(0)151 606 1000
Fax: +44(0)151 606 1122
email: info@cqr.co.uk
www.cqr.co.uk

A member of



#### distributed by: