



# HDUB16RP

## 16 Channel Passive Balun Rack

*The HDUB16RP is a 16 Channel Passive HD (Non-Amplified) Video UTP Transceiver that allows transmission of real time and high performance colour or monochrome CCTV video. The device is 1U rack-mountable, ideal for multi-point transmission.*



HDUB16RP

### Key Features

- Passive, No Need for a Power Supply
- AHD, HD-CVI, HD-TVI, CVBS 4 in 1 Compatible Design
- RJ-45 or Terminal Block to UTP Cable Connectivity
- Compact Design, 1U Rack Mountable
- Plug and Play
- Surge Protection and Interference rejection

# Technical Specification

Model Number	HDUB16RP
Transmission Channel	16 Channel
Transmission Distance	AHD-L/M (720p): 250m, AHD-L/M (960p): 250m AHD-H (1080p): 250m, Anaglogue Video: 500m HD-CVI (720p): 370m, HD-CVI (1080p): 100m HD-TVI (720p): 200m, HD-TVI (1080p): 200m
Video Connector	BNC-F
UTP Cable Video Connector	8 Pin Green Terminal Block, RJ-45
Compatible With	AHD, HD-CVI, HD-TVI, CVBS, PAL, NTSC, SECAM Video
Signal Transmission Band	0-70MHz
Interference Rejection	>60dB
Video Connector Surge	2KV (Common Mode) Per: IEC61000-4-5
UTP Cable Connector Surge Protection	2KV (Different Mode) per: IEC6100-4-5
ESD	Contact Discharge: 6000V Air Discharge: 8000V Per: IEC61000-4-2
Operation Temperature	0 ~ 55°C
Storage Temperature	-40°C ~ 85°C
Humidity	0~95% (Non-Condensing)
Dimensions (L x W x H)	430 x 100 x 44.5 (mm)

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

## Dimensions (mm)

