

Product Code: HDVIP32R

Description: 32 Channel HD 4TB NVR


System		Video & Audio	
Dimensions	380mm x 340mm x 50mm	Video Input	16CH
Operating System	LINUX	Audio Output	1CH
Recording Bandwidth	320Mbps	Line In	1CH
POE	16CH (<100 Metres per Channel)	Playback & Backup	
Power		Sync Playback	5 Megapixel
Power Output	48V DC/4.2A	Backup Mode	Network / 2 x USB2.0 / 1 x USB3.0 / e-SATA
PoE Ports	16 Ports	Network	
Max. PoE Consumption Available	280 Watts	Ethernet	RJ-45 port (1000M)
NVR Power Consumption	<7W (Without Hard Disk)	Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
NVR Power Source	IEEE802.3af	Network Monitoring	Web browser, Client Software, Android & IOS
Recording		Storage	
Compression	H.264 / H.265 Selectable	Internal HDD	<16TB HDD
Resolution	5 Megapixel	External HDD	e-SATA < 4x6TB
Record Rate (Main Stream)	5 Megapixel	Environment	
Recording Mode	Manual/Motion Detection/Schedule	Operation Condition	0°C to +55°C / 10% – 90%
Interface			
	16CH		
Alarm Out	1CH		
Data	RS485		
Display			
Video Output	1 x HDMI, 1 x VGA		
Display Split	1/4/6/8/9/10/13/14/16/17/19/22/25/32/36		
Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160		

Accessories

IPIN1POE	1 Channel POE Injector (30W)
IPSW4POE	4 Channel POE Switch (60W)
IPSW8POE	8 Channel POE Switch (120W)
HDVIP1632RRMB	Rack Mount Bracket For Models: HDVIP16R, HDVIP32R
CABIP10	10 Metre CAT-5e External Use Data Cable
CABIP20	20 Metre CAT-5e External Use Data Cable
CABIP40	40 Metre CAT-5e External Use Data Cable
CABIP80	80 Metre CAT-5e External Use Data Cable
CABIPCOUP	RJ45 CAT-5e Data Cable Coupler

Supplied

System Power Supply & Power Lead
 Software CD
 Manual
 HDMI Lead
 Mouse Control
 Remote Control (Batteries Included)

Additional Information: Only 16 ports are available on the unit
 Recommended 2 x IPSW8POE, and 1 x IPSW4POE is used in conjunction for full operation of the HDVIP32R

