



Applications

- > Programming and operating VIDEOFIED™ security systems.

Electrical Data

Power requirements	One battery
Battery type	Lithium 3.0V CR123
Battery life	4 years
Technology	WiseLink®
Radio type	Spread Spectrum Bidirectional RF
Operating frequency	868/915 MHz
Transmission security	AES algorithm encryption
Supervision	polled signal every 8 minutes
Antenna	Integrated
Tamper detection	Wall and cover tampered
Operating temperature	0°/+40°C (32°/104°F)
Shocks	IK07
Protection	IP30
Maximum relative humidity	70%, non-condensing
Approvals	CE (SD200) / UL 268 (SD600)

Physical Data

Material	ABS-ULV0
Height	55 mm
Diameter	120 mm
Weight	185g (without batteries)

Features

- > Recording by push button under the cover.
- > Internal serial Nb, and bar code.
- > Opening, ripping off and normally closed input.
- > Built in 85 dB.
- > Optical detection of visible particles.
- > Efficiency : 55m².

Installation/Mounting

Wall fixing	2 screws
Positioning	By oblong holes
Front cover closing	By bottom screws
Mounting adjustment	No, pre positioned



EMEA SALES

2, rue Alexis de Tocqueville
92160 ANTONY
FRANCE
Phone +33 (0)1 55 59 10 25
Fax +33 (0)3 90 20 66 36

USA SALES

4455 White Bear Parkway, Suite 700
White Bear Lake, MN 55110
USA
Phone 877-206-5800
Fax 651-762-4693

