

**IX0101CO****SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM**

Front plate for Switch entrance panel in 2.5 mm thick brushed AISI 316 stainless steel, designed to house SimpleKey or third-party access control readers. Adapter art. 1250U (supplied) offers the option of using the audio or audio/video module (not supplied), depending on the type of wiring applied (Simplebus digital 2-wire or ViP). Complete with 1 pre-fitted, pre-wired button. White LED nameplate backlighting. IK08 protection rating. To be finished with flush-mounted box or surface-mounted casing. Panel dimensions: (L x H): 150x262.7 mm. Hole dimensions: 40x40 mm.

AWARDSDESIGN
MILANO



IX0101CO

SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM

GENERAL DATA

Type	Monoblock
Height (mm)	262.7
Width (mm)	150
Depth (mm)	2.5
Product color	Steel
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.1621, Art.1622, Art.1622VC, Art.4680C, Art.4681
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	White

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08



IX0101CO

SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III