



KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



The kit includes: three Mini series door-entry phones art. 2702W, a transformer art. 1200, an Extra series external unit designed for 2/4 call buttons art. ET5100, 4 single buttons for Extra entrance panel art. ET9211. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the corresponding accessories supplied with the kit.

AWARDS



DESIGN
MILANO



KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

PRODUCTS IN THE KIT



ET5100 EXTRA 4+N ENTRANCE PANEL PREPARED FOR 2/4 BUTTONS

Extra series audio entrance panel with stainless steel cover and nameplate backlighting. To be completed with single button art. 9211 (pack of 4 units) to offer 4 call buttons, or with double-height button art. 9210 (pack of 2 units) to offer 2 call buttons. The entrance panel can be surface-mounted or flush-mounted using the relevant accessories supplied. Traditional 4 + N wiring system. Dimensions (W x H x D): 95x165x6.5 mm (flush) - 25 mm (surface).

GENERAL DATA	
Type	Monoblock
Flush-mounted	Yes
Wall-mounted	Yes



KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



2702W 2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light.
Dimensions: 105x191x28 mm

GENERAL DATA

Height (mm)	190
Width (mm)	105
Depth (mm)	28
Product color	White
Type of finishing materials	Plastic
Product weight (g)	260
Wall-mounted	Yes
Desk base-mounted	Yes

COMPATIBLE SYSTEMS

Traditional system	Yes
--------------------	-----

AUDIO FEATURES

Microphone	4mm (Ø), Omnidirectional
Loudspeaker	0.50mm, 0.5W

ELECTRICAL CHARACTERISTICS

Supply voltage	15÷16VDC
Absorption in stand-by (W)	3
Maximum absorption (W)	6

HARDWARE FEATURES

Type of buttons	Mechanical
Service buttons	Lock-release



KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT

HARDWARE FEATURES

Clamps	S 2 3 4 P1 P2
Total buttons (n°)	2

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	III
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES

Door opener	Yes
Silent mode (Privacy)	Yes
Loudspeaker volume control	Yes
Microphone volume control	Yes
Ringtone volume control	Yes
Electronic bell	Yes



KAE5063

EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT



1200 TRANSFORMER 10VA 0-230V/0-12V

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES

Supply voltage	230
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9

GENERAL DATA

Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	15
-----------------------------	----

**KAE5063****EXTRA-MINI 5-WIRE THREE-FAMILY AUDIO KIT****ACCESSORIES****ET9150 Flush-mounted box for Extra entrance panel kit**

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm

**ET9160 Wall bracket for Extra entrance panel kit**

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm

**ET9211 4 SINGLE BUTTONS FOR EXTRA ENTRANCE PANEL**

Single buttons to complete the Extra series entrance panel with traditional wiring art. ET5100. Pack of 4 pcs.

**1229 EXTENSION SOUNDER**

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfaced mounted or on civil series 503 box. Dimensions: 110X75X29 mm.