

- ✓ Hush feature allows nuisance alarms to be temporarily silenced (e.g those caused by cooking or steam)
- ✓ Ionisation sensing technology
- ✓ Battery operated (9V battery supplied as standard)
- ✓ Test/Reset Button Tests alarm circuit operation

Product description

This smoke alarm has a modern design and benefits from the hush feature that allows nuisance alarms (such as those caused by cooking or steam) to be temporarily silenced.

At least one smoke alarm should be installed on each level of the home and in areas close to bedrooms. A working smoke alarm provides the earliest possible warning of smoke or fire in the home and can double a person's chance of surviving a house fire. There are many different types of smoke alarms with various features for enhanced usability.

Kidde recommends that for maximum protection both ionisation and photoelectric smoke alarms are installed in the home.

* Ionisation sensing alarms may detect invisible fire particles (associated with fast flaming fires) sooner than photoelectric alarms. Photoelectric alarms may detect visible fire particles (associated with slow smouldering fires) sooner than ionisation alarms.



Order Code	i9060UK-C
Power Supply	Battery operated (9V battery supplied as standard)
Temperature Range	0°C to +40°C
Humidity Range	Up to 93% Relative Humidity (RH)
Alarm Dimensions	124mm x 124mm x 36mm
Alarm Weight	0.18kg
Approvals	Approved by LPCB to EN14604 / CE approved
Warranty	5 years
Dimensions (packaged)	215mm x 190mm x 50mm
Weight (packaged)	0.26kg
UPC Barcode	0-047871-164219
Case Quantity	3
Case Dimensions	202mm x 158mm x 296mm
Case Weight	0.9
ITF Outer Code	200-47871-164213



EN14604
LPCB Ref No. 904a/07

