

**KVV8111****VISTO VIP KIT WITH POWER SUPPLY UNIT**

Single-family kit with smart Wi-Fi doorbell complete with power supply unit. After connecting to the Wi-Fi network, you will be able to receive calls straight to your smartphone and tablet using the Comelit app. With the Comelit app you will always be in touch with what's happening at home, whether you are out and about in town or even in another country. The Kit consists of 1 Visto ViP Wi-Fi external unit art. VS8111 and 1 power supply unit art. 1595.



KVV8111

VISTO VIP KIT WITH POWER SUPPLY UNIT

PRODUCTS IN THE KIT



VS8111 VISTO WI-FI EXTERNAL UNIT. VIP SYSTEM

Wi-Fi video entry external unit for use in Comelit ViP systems, complete with adapter allowing use of the power supply for the existing bell (12-20 VAC or 12-33 VDC) and allowing interfacing with the existing bell. Depending on the system configuration, you can receive video entry phone calls on ViP monitors or directly on smartphones and tablets via the Comelit app. With the Comelit app, you are always in touch with what is going on at your home, whether you are in town or even in another country.

GENERAL DATA	
Type	Monoblock
Height (mm)	136
Width (mm)	47
Depth (mm)	32
Product color	Dark Graphite RAL9011
Wall-mounted	Yes
COMPATIBLE SYSTEMS	
ViP	Yes
AUDIO FEATURES	
Technologies implemented	Full-Duplex, Echo canceling, Noise reduction
CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	1.6
Angle of view (H x V - °)	170 (diagonal)
Sensitivity (lux)	2
Video resolution (H x V - pixel)	



KVV8111

VISTO VIP KIT WITH POWER SUPPLY UNIT

CAMERA FEATURES

Video compression	H.264
-------------------	-------

ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	12÷33 VDC
Maximum absorption (W)	6

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Clamps	+ - NO C
Removable terminals	Yes
Number of outputs (n°)	1
Type of outputs	Relay (C-NO, 1A@30VDC)

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	2.4 GHz
--------------------------	---------

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	0 ÷ 75
Environmental class	III
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS



KVV8111

VISTO VIP KIT WITH POWER SUPPLY UNIT

Visual indications of system status	Yes
-------------------------------------	-----



KVV8111

VISTO VIP KIT WITH POWER SUPPLY UNIT



1595 120-230VAC / 33VDC POWER SUPPLY UNIT

Power supply unit with input of 120÷230VAC, 33VDC output with 500mA continuous and 1.2A inrush current for video door entry panel. Equipped with internal protection against overcurrent and short circuits. Dimensions: 71.7x90x62 mm (4 DIN modules).

MAIN FEATURES

Supply voltage	120÷230 VAC
Output supply voltage	33VDC
Max. current delivered (A)	0.5
Maximum inrush current (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

GENERAL DATA

Height (mm)	62
Width (mm)	71.7
Depth (mm)	90
Type of finishing materials	Plastic
Product color	White
Operating temperature (°C)	-20 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes



KVV8111

VISTO VIP KIT WITH POWER SUPPLY UNIT

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	60
-----------------------------	----