



Fig. 1 - L20A Door Loop



Fig. 2 - L20B



Fig. 3 - L40



Fig. 4 - L20BA Door Loop



Fig. 5 - L60A Door Loop



Fig. 4 - L60 Door Loop



Fig. 5 - L70ARM Door Loop
(Special Armoured Cable)



Fig. 6 - L80

	Model			
	L10	L20	L30	L40
Grade 2 Class II	●	●	●	●
Crimped End Cables	●	●	●	●
2 x 4 Way J. Boxes	●	-	●	-
2 x 6 Way J. Boxes	-	●	-	●
250mm Coiled Cord	-	-	●	●
305mm Straight Cord	●	●	-	-
Extendable to 1750mm with J.B	-	-	●	●

	Model			
	L50	L60	L70	L80
Grade 2 Class II	●	●	●	●
Crimped End Cables	●	●	●	●
2 x 4 Way J. Boxes	●	-	-	●
2 x 6 Way J. Boxes	-	●	●	-
2 x 6+2 Way J. Boxes	-	-	●	-
450mm Armoured Sleeve	-	-	●	-
250mm Coiled Cord	-	-	-	-
500mm Coiled Cord	●	●	-	-
1000mm Coiled Cord	-	-	-	●
Extendable to 1750mm with J.B	-	-	-	-
Extendable to 3500mm with J.B	●	●	-	-
Extendable to 5000mm	-	-	-	●

Description:
Door Loops, Straight & Coiled

Materials:
HIPS & PVC Cable
Moulded on Grommet to fit
Junction Box knockout

Conductors:
Cadmium Copper tinsel PVC insulated
Minimum radial thickness 12mm

Connectors:
6BA Open Ended

Temperature Range:
-40°C - +50°C

Voltage Range:
1 - 100v DC
125v AC Max

Switching Current
500mA Max DC
500mA Max AC

Colours:
White
Brown (Suffix B)
L80 - Black only

Variations:
Suffix A for no Junction Box

KNIGHT
FIRE & SECURITY PRODUCTS LTD
email: info@knightplastics.com

Unit 84 Seawall Road Ind. Estate
Cardiff UK CF24 5TH
Tel: 0 (00 44) 29 20 48 81 29
Fax: 0 (00 44) 29 20 48 91 32

Drawing No: **L10-L80**
Door Loops
Chris Moorman
Date: 11/02/08

All units in mm
Do not scale



© Knight Fire & Security Products Ltd
All cases of TM Infringement will be pursued.