



The LED Maintained Emergency Recessed Fitting is available in 2.5W LED, with a 297 lumen output and has an emergency maintained duration period of at least 3 hours.



Specification

Voltage:	220-240V	
Wattage:	2.5W	
Power Consumption:	6.5W	
LED:	50pcs of Ø5 LED	
Lumen Output:	297lm (201lm in emergency mode)	
Colour Temp.:	6000-7000K	
Emg. Duration:	≥ 3 hours	
Charging Duration:	24 Hours	
Guarantee:	1 year	
IP Rating:	IP20	
Power Factor:	0.429	
Battery:	Nickel cadmium SC3.6V 1500mAh	
Material:	Steel body, polycarbonate diffuser	
Working Temp:	0°C - 40°C	
Extra Info:	3V Deep discharge protection. 4.3V Overcharge protection. Weight: 1585g. Ø 20mm Cable entry. Class I. Cut out: 340 x 120mm. Maintained - can be converted to non-maintained by removing switch live link.	

MODEL	WATTAGE	EMERGENCY	LUMEN OUTPUT	DIMENSIONS (L x W x D mm)
LFACLED502F	2.5W	YES 3 HRS	297lm	412 x 143 x 90
EL	EXIT LEGEND FOR 8W BULKHEADS			