

DAYLIGHT SENSOR

For full specification see page 48.

Applications

- Factories
- Warehouses
- Leisure Centres



Material:	Polycarbonate
Life Expectancy:	50,000 Hours
Working Temperature:	-35°C - 70°C
HLBDS	High and Low Bays

LED HI-LO BAY MICROWAVE SENSOR + REMOTE CONTROL



For full specification see page 49.

Applications

- Factories
- Warehouses
- Leisure Centres



Working Temperature:	-35°C - 70°C	
HLBMS	Hi and Low Bays	
HLBMS-RC	Remote Control	

INTERNAL LED MICROWAVE SENSORS

The built in microwave sensor for Non Corrosive Fittings and Batten Fittings with fully customisable settings.

Applications

- Commercial Kitchens
- Educational Providers
- Retail




Guarantee:	3 Years	
WFLEDMS	115 x 32 x 23	
WFLEDMS-1	115 x 37 x 25	

EXTERNAL MICROWAVE SENSOR

The microwave sensor designed for installation to the outside of the light fitting for energy saving. The detection area, hold time and lux sensor are adjustable to suit the installation requirement.

Applications

- Commercial Kitchens
- Factories
- Hospitality



Material:	Polycarbonate	
Life Expectancy:	30,000 Hours	
Working Temperature:	-20°C - 60°C	
MSLEEXT	Non-Corrosive Fittings and Batten Fittings	