



Fig. 1 - P01 Pass Key Switch



Fig. 2 - P03 Pass Key Switch



Fig. 3 - P05 Pass Key Switch

	Model				
	P01	P02	P03	P04	P05
Grade 2 Class III	-	●	-	●	-
Grade 3 Class III	●	-	●	-	●
Diecast Aluminium Body	●	●	-	-	-
Polycarbonate Body	-	-	●	●	●
Micro-Switch	●	●	●	●	●
Tampered	●	●	●	●	●
Metal Key	●	●	●	●	●
Different Keys	●	-	●	-	-
Suited Key	-	●	-	●	●
Spare Keys to order	●	●	●	●	●
Internal LED's	-	-	-	-	●
Max Voltage 250vAC	●	●	-	-	-
Max Current Amps	2	2	-	-	-
Supply Voltage 125vAC	-	-	●	●	●
Max Current Amps	-	-	10	10	10
Supply Voltage 250vAC	-	-	●	●	●
Max Current Amps	-	-	6	6	6
Dimensions	Length 90	Width 38	Height 30mm		

Description:
Grade 2 & 3 Class III
Pass Key Switch

Materials:
Diecast Aluminium or Polycarbonate
2 x Metal Keys Provided

Temperature Range:
-40°C to +50°C

Tamper:
Microswitch

Switching Current
(Please refer to inset table)

Voltage Range:
(Please refer to inset table)

Colours:
Lacquered Aluminium
White Plastic

Finishes:
Aluminium or Plastic

Fixing Screws Provided

KNIGHT
FIRE & SECURITY PRODUCTS LTD
<mailto:info@knightfireandsecurity.com>

Unit 84 Seawall Road Ind. Estate
Cardiff UK CF24 5TH
Tel: 0 (00 44) 29 20 48 81 29
Fax: 0 (00 44) 29 20 48 91 32

Drawing No: **PO1-5 Pass Key Switches**

Drawn: *Chris Moorman*
Date: *28/05/09*

All units in mm
Do not scale



© Knight Fire & Security Products Ltd
All cases of ™ Infringement will be pursued.