

Product Code: PA16621

Description: Standard Analogue 24 hr Timer



General Information

| | |
|--|-----------------------|
| Full Dimensions | 72mm x 94.5mm x 53mm |
| Panel Dimensions | 72mm x 72mm |
| Display | Mechanical Dial |
| Connection by cage terminals, section of conductors | 1 - 6 mm ² |
| Time Base | Quartz Crystal |
| Accuracy of Operation | 1 sec / 24 Hour |
| Warranty | 3 Years |

Power

| | |
|-----------------------------|--|
| Operating Voltage | 230VAC |
| Power Consumption | 0.5A~ |
| Power Reserve @ 20°C | Approx. 200 Hours |
| IEC Protection Class | Class II when installed according to regulations |

Construction

| | |
|------------------------------------|----------------------------------|
| Material | Self-Extinguishing Thermoplastic |
| Fixing | Surface, Panel, or DIN |
| Distribution Board Mounting | 35mm DIN-rail (DIN EN 60715) |

Outputs

| | |
|----------------------------|-------------|
| Contact Type | SPDT |
| Panel Dimensions | 72mm x 72mm |
| Total Switch Rating | 16A (3) A |
| Resistive Load | 16A 250V |

Outputs

| | |
|--|------------|
| Voltage Free Inductive Load (cos φ = 0.6) | 3A 250V |
| Incandescent Lamps | 1000W 250V |
| Squirrel-Cage Motor | 350W 250V |

Programming

| | |
|-----------------------------|-------------------------|
| Programming Schedule | 24 Hour |
| Available Operations | 72 Operations |
| Switching Modes | ON and OFF |
| Switching Accuracy | 1 Minute and 30 Seconds |

Environment

| | |
|------------------------------|---------------------|
| Ingress Protection | IP20 (DIN EN 60529) |
| Operating Temperature | -10°C to 50°C |

Accessories

| | |
|---------------------|-------------------------------|
| 95587 | Panel Converting Mounting Kit |
| MAGPRO-HD1 | 0 |
| MAGPRO-HSD1 | 0 |
| MAGPRO-WS | 0 |
| MAGPRO-WSS | 0 |
| MAGPRO-WSS23 | 0 |

Features

- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- 100 hour battery reserve
- Programming by 15 min captive segments
- Manual override with automatic return to program
- Contact status display
- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- 100 hour battery reserve

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch, B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espuk.com | **W:** espuk.com