

Product Code: PA16622

Description: Standard Analogue 24 hr Timer



General Information

Full Dimensions	72mm x 94.5mm x 53mm
Panel Dimensions	72mm x 72mm
Display	Mechanical Dial
Connection by cage terminals, section of conductors	1 - 6 mm ²
Time Base	Quartz Crystal
Accuracy of Operation	1 sec / 24 Hour
Warranty	3 Years

Power

Operating Voltage	230VAC
Power Consumption	0.5A~
IEC Protection Class	Class II when installed according to regulations

Construction

Material	Self-Extinguishing Thermoplastic
Fixing	Surface, Panel, or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)

Outputs

Contact Type	SPDT
Panel Dimensions	72mm x 72mm
Total Switch Rating	16A (3) A
Resistive Load	16A 250V

Outputs

Voltage Free Inductive Load (cos φ = 0.6)	3A 250V
Incandescent Lamps	1000W 250V
Squirrel-Cage Motor	350W 250V

Programming

Programming Schedule	24 Hour
Available Operations	72 Operations
Switching Modes	ON and OFF
Switching Accuracy	1 Minute and 30 Seconds

Environment

Ingress Protection	IP20 (DIN EN 60529)
Operating Temperature	-10°C to 50°C

Accessories

95587	Panel Converting Mounting Kit
MAGPRO-HD1	0
MAGPRO-HSD1	0
MAGPRO-PROG	Address Programming Tool For MAGPRO Devices
MAGPRO-DBSC	Terminal Cover

Features

- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- Programming by 15 min captive segments
- Manual override with automatic return to program
- Contact status display
- Voltage free 16A changeover contact
- Suitable for Surface, Panel or Din rail mounting
- Programming by 15 min captive segments
- Manual override with automatic return to program
- Contact status display

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom
T: +44 (0)1527 515150 | **F:** +44 (0)1527 515143
E: info@espu.com | **W:** espu.com