The PAC Wireless Gateway

With over 35 years' experience in delivering outstanding security products, at PAC we strive to bring out flexible solutions that our customers can truly rely on. Being able to control access in your premises online is no longer just a convenience but a necessity, that is why we bring you the PAC Wireless Gateway.

The Gateway has been designed to complement and enhance the functionality of our new EL Smart Door Handle. The device provides a means of wireless communication between the controlling PC and the EL Smart Door Handle.

The PAC wireless Gateway is an IP appliance which can be powered by either a local PSU or a POE+ 802.3 at enabled network switch. Utilising PAC's own propriety 2.4 GHz frequency to wirelessly communicate with the EL Smart Door Handle, the Gateway enables remote control of ID administration and receives all access events in real time.

As we continue to bring out breakthrough technologies coupled with solid designs and reliable solutions, PAC's commitment to providing unbeatable security is stronger than ever.

Our unique, embedded web portal for the Gateway is a delivery on that commitment. It enables the setup and configuration of the device. The IP address, time zone, password and network communication port can all be managed within the portal. This enables a seamless and secure communication method.

The Gateway is provided with a small integral antenna which provides a field of coverage of up to $25m^{2*}$. For installations where the location of the Gateway is awkward due to the design of the building or installation restrictions, we also provide a ceiling mount antenna as a flexible installation option.

- Web-based configuration
- LAN Communication Interface POE+ 802.3at compatible
- Allows connection to PAC EL Smart Door Handle
- Additional Ceiling Mount Antenna option

Compatible with:



Contact our dedicated customer services team on:

+44 (0) 161 406 3400

to find out how you can start benefiting from a tailored PAC security system that accommodates your business' requirements.

"A robust door entry solution, which is able to thwart the more resourceful individuals – backed up with fast and effective excellent customer service and innovative product solutions."

Part Numbers:

880080000 — Gateway including small Antenna (no PSU) 880080002 — Gateway Ceiling Mount Antenna (no PSU) 880080001 — PSU for Gateway — UK/EU Plug







The Wireless Gateway & Ceiling Mount Antenna SPECIFICATIONS

| Product Part Numbers | Wireless Gateway - 880080000PSU - 880080001 | Ceiling Mount Antenna - 880080002 |
|----------------------------------|---|--|
| Dimensions | 109.1mm x 117mm x 34mm | Diameter 117mm |
| Weight | Wireless Gateway - 181gPSU - N/A | N/A |
| Environment | Internal use only | |
| Operating Voltage | 24V DC @ 0.5Amp | |
| Operating Temperature | 60°C to 0°C | |
| Certification | CE compliant under R&TTE Directive | |
| Boxed Product Contents | Gateway: Product and instruction manualPSU: PSU only | Product and 6m cable |
| Transmitter Power | 12.705741mW | |
| Interface | LAN Communication TCP/IP (IEEE 802.3) | N/A |
| Wireless Communication Interface | IEEE 802.15.4 (2.4GHz) | N/A |
| Wireless Communication Protocol | STANLEY Propriety | N/A |

