

PB20

2m - 180° AIR Beam Tower (single sided) including installation kit.

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 1 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP3)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 12 pcs (EP3) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 1 pcs (EP3)
15. Cable gland PGM20 : 1 pcs (EP3)
16. M8x16 DIN933 : 4 pcs (TA3)
17. Side bracket <2m : 2 pcs
18. M8 DIN 985 : 4 pcs (TA3)
19. M8 DIN 125 : 4 pcs (TA3)
20. M4x12 DIN 7985 : 8 pcs (C3)
21. Bracket : 4 pcs
22. dia.2.9x16 DIN 7981 : 8 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2)



Details

- 2m height
- 180° view
- CE certified product

PB20

2m - 180° AIR Beam Tower (single sided) including installation kit.

Technical specifications

General

Accessory group	Perimeter / Outdoor
Type	Mounting

Electrical

Operating voltage	12 to 24 V
Power supply type	VDC

Physical

Physical dimensions	1970 x 130 x 150 mm
Net weight	5.75 kg

Environmental

Operating temperature	-15 to 50 °C
-----------------------	--------------

Voltage

	12 to 24 VDC
--	--------------

Angle of view

	180°
--	------

Tamper switch output

	CO (change over)
--	------------------

Operating temperature

	-15 to +50°C
--	--------------

Material

	Aluminium, plastic (polycarbonate, ABS)
--	---

Dimensions (HxWxD)

	197 x 13 x 15cm
--	-----------------

Weight

	5.75 kg
--	---------