



RETROFIT HANDLES

▶ A WIDE RANGE OF RETROFIT HANDLES SUITABLE FOR ALL YOUR NEEDS

PBO400RN40 400MM retrofit handle (1 x 400Kg)



**PATENTED,
BREVETÉ**

- **NF S 61-937.**
- **Ultra-quick installation.**
- **400mm handle.**
- **Pre-drilled sections (adjustable).**
- **Width overlapping the previous installations.**
- **Terminal block.**

- Holding force: 400kg.
- Dimensions (L x W x D): 400 x 126 x 68mm.
- Satin-finished silver anodised aluminium section with possibility of RAL (Option).
- End caps for the ends of the handles.
- Glass door option: UBKPBO400RN40.
- Input voltage: 12/24V dc.
- Consumption of the 400 kg electromagnetic lock:
 - 12V dc = 550mA.
 - 24V dc = 275mA.



RoHS

CE CE Certification



WEEE

-20°C to +70°C


H.R.V.
HIGH RESISTANCE
TO VANDALISM

**Recommended
power supplies**



CODE	REFERENCE	DESCRIPTION
F0519000046	PBO400RN40	400MM 1x400KG RETROFIT HANDLE
F0517000012	UBKPBO400RN40	2 x 400MM UBK KIT
F0519000017	RAL	RAL COLOUR OPTION

600MM retrofit handle (2 x 400Kg) PBO800RN60



H.R.V.
HIGH RESISTANCE
TO VANDALISM

**Recommended
power supplies**



RoHS



WEEE

CE

CE Certification



-20°C to +70°C

- **NF S 61-937.**
- **Ultra-quick installation.**
- **600mm handle.**
- **Pre-drilled sections (adjustable).**
- **Width overlapping the previous installations.**
- **Terminal block.**

- Holding force: 2 x 400 kg.
- Satin-finished silver anodised aluminium section with possibility of RAL (Option).
- End caps for the ends of the handles.
- Glass door option: UBK (See P. 254).
- Dimensions (L x W x D): 600 x 126 x 68mm.
- Input voltage: 12/24/48V dc.
- Consumption par ventouse 400kg:
 - 12V dc = 550mA,
 - 24V dc = 275mA.
- Consumption for the two 400kg electromagnetic locks en 48V dc: 275mA.



**PATENTED,
BREVETÉ**

CODE	REFERENCE	DESCRIPTION
F0519000056	PBO800RN60	600MM 2x400KG RETROFIT HANDLE
F0519000087	PBO800RN60OPTION	600MM 2x400KG RETROFIT HANDLE FOR OPTION
F0519000017	RAL	RAL COLOUR OPTION

* Refer to Limited Lifetime Warranty Conditions.