

SPECIFICATIONS



	PORTACODE KEYPAD, SILVER	PORTACODE KEYPAD, CHAMPAGNE
REFERENCES	PCA327-RS	PCD327-RS
MECHANICAL CHARACTERISTICS		
Facia dimensions (HxWxD)	216 x 120 x 2.5 mm	
Flush box dimensions (HxWxD)	165 x 95 x 45 mm	
Surface box dimensions (HxWxD)	217 x 121 x 17 mm	
Weight	1300g	
Material	ZAMAC	
Colour	Silver	Champagne
IP protection	IK09 / IP65	
ELECTRICAL CHARACTERISTICS		
Voltage	12VDC – 24VDC	
Consumption	150 mA	
Power supply	12VDC / 2A	
Relay	2no 5 Amp rated NO/NC programmable	
Operating temperature	Operating -20°C to 55°C	
FEATURES		
Voice output messages	2no with 10 volume level settings	
Bus	Max length 400 metres using Class E (CAT6) U/UTP in series	
Capacity	90 user codes, length 4–8 digits/characters any mix	
Calendar function	8no week types with baticonnect.com	
Programming	www.baticonnect.com available 24/7/365	



08000 156496
 sales@ipdooreentry.co.uk
 www.ipdooreentry.co.uk
 f ipdooreentry

IP Door Entry Limited
 Unit DC4 Prologis Park
 Eastman Way
 Hemel Hempstead
 HP2 7DU



24/7/365
 www.baticonnect.com