Product data sheet



PS5VDC2A-UK

5 VDC 2 AMPS. Wall plug PSU - UK

Overview

UTC Fire & Security's wide range of power supplies provide solutions for all the majority of various applications. Available in wall format with adaptors, UTC Fire & Security supplies can be used with all major power plugs. Solutions include both in wall and "power brick" configurations. Switching supplies include advanced technology and power savings, meeting Level IV (4) International Efficiency in compliance with California Energy Commission, Energy Star and the EU Code of Conduct for external power supplies. Supplies can be mixed and matched to a variety of UTC Fire & Security products to meet installation requirements.

Supplies are available in both +48 Volt DC, +12 Volt DC and +5 Volt DC models, meeting a wide range of price, installation and wall prongs for world-wide operations. With UTC Fire & Security power supplies, the power is in your hands.



Details

- Compact power supplies for standalone fiber links or Media Converters
- Low voltage outputs
- Models for Europe and UK region
- CE approved
- UL approved
- CSA approved
- Wall plug

PS5VDC2A-UK 5 VDC 2 AMPS. Wall plug PSU - UK

Technical specifications

Electrical	
Mains input	90 to 264 VAC
<u> </u>	
Output	
Power output voltage	5 VDC
Power output current	2 A
mains	
Physical	
Colour	Black
Form factor	External adapter
Standards & Regul	ation
Compliancy	CE, REACH, RoHS 2, WEEE
Specifications	
	00. 2644.46
Input Voltage :	90 - 264V AC
Frequency Range :	47-63 Hz 5V DC
Output Voltage : Current :	2 A
	In Wall
Type:	
Dimensions (mm):	85 x 72 x 32
Weight:	106 gr
Standards Conform	nance
EMC:	CISPR 22 Class B
EMC:	EN55022 Class B
EMC:	EN61204-3 Class B
EMC:	FCC parts 15 Class B
BSMI : EMS requirementsEN55024	
:	
BSMI : EMS requirementsIEC-61000-4-2	
DCML FMC requirementalFC 61000 4.2	
BSMI : EMS requirementsIEC-61000-4-3 :	
BSMI : EMS requirement	csIEC-61000-4-4
:	
BSMI : EMS requirementsIEC-61000-4-5	
:	
BSMI : EMS requirement	csIEC-61000-4-6
:	
BSMI : EMS requirement	tsIEC-61000-4-8
:	
BSMI : EMS requirement	tsIEC-61000-4-11
Cofoby Dogy:	150 60050
Safety Requirements :	IEC 60950
Safety Requirements :	UL 60950-1TUV
Safety Requirements :	Efficiency Level IV
Regulation Compliance : FCC Part 15	
Regulation Compliance	
Safety:	cUL
Safety :	UL

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

