


PTDOME-CAM - Indoor Wi-Fi PT Dome Camera

Look around anytime from anywhere



Key features

- Full-HD 1080p
- Pan & tilt rotation
- Wide Dynamic Range (WDR)
- Auto Day/Night mode
- 10m Infrared (IR) range
- Real-time HD video on the move
- Easy setup

Partcode	PTDOME-CAM/4
Camera	
Resolution	2 Megapixel
Lens	4mm (PTDOME-CAM/4), horizontal field of view: 90°
Day & Night	IR cut filter with auto switch
Digital Noise Reduction (DNR)	3D DNR
Wide Dynamic Range (WDR)	120dB
Compression Standard	
Video Compression	H.264 / MJPEG / H.264+
Dual Streams	✓
Image	
Max. Resolution	1920 x 1080p (25 fps)
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
Back Light Compensation (BLC)	Support, zone configuration
Network	
Network Storage	NAS (Support NFS, SMB/CIFS), ANR
Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General Function	One-key reset, Flash prevention, Dual Stream, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filtering, Anonymous Access
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet port
On-Board Storage	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
Wi-Fi	
Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4GHz ~ 2.4835 GHz
General	
Operating Conditions	-10°C to +40-°C
Power Supply	DC12V or PoE (803.3af)
Power Consumption	Max. 5W (Max. 7W with IR cut filter on, Max 9W with pan & tilt rotation)
IR Range	Up to 10 meters
Dimensions	Φ119.93 x 87.08mm
Weight	500g (1.1lbs)
SAP Code	PTDOME-CAM/4: 311300208