

PRODUCTS

REMTH

Remote Test and Hush Unit

DESCRIPTION

Wired Remote Test and Hush unit that allows for system testing of all interconnected alarms or to hush unwanted alarms from one location



Updated REMTH model available soon!

KEY FEATURES

- Separate Test and Hush buttons
- One-man test via Latch selectable test alarm feature
- LED displays red or green dependant on status (green = mains healthy, red = test, hush or locate)
- Wall mounted in single gang back box (not supplied)
- Selectable hush period 8 or 15 minutes

WHERE TO USE

For convenient test and hush of multiple alarms from one single location. This unit should be installed by a qualified electrician only, in conjunction with hard-wired smoke and heat alarms.

GENERAL FEATURES

Model	REMTH
Power Supply	230V mains-powered
Temperature Range	0°C to + 40°C
Humidity Range	Up to 93% Relative Humidity (RH) non-condensing
Unit Dimensions	87 x 87 x 15mm
Unit Weight	58g
Warranty	6 years
Approvals	CE tested and certified
Associated Standard	BS 5839 Part 6 Grade D

OPTIONAL PRODUCT

As an alternative to this wired unit, installers may use the following Kidde wireless remote test and hush switch for use with 'Slick' mains alarms only:

RTH	For wireless test and hush of interconnected mains alarms
	For further information see RTH datasheet.

For more information or to contact Kidde Sales:

PRODUCTS

REMTH

Remote Test

and Hush Unit



COMPATIBLE WITH

KF1 / KF1R 1SFW / 1SFWR

KF2 / KF2R 2SFW / 2SFWR 423/9HIR KF3 / KF3R 3SFW / 3SFWR 423D/9HIR

NOTES

			_
			_

PACKAGED SPECIFICATIONS

	PLAIN BOX	
Order Code	REMTH	
Pack Dimensions	88 x 88 x 33mm	
Pack Weight	65g	
UPC Barcode	n/a	
Case Quantity	6	
Case Dimensions	170 x 135 x 140mm	
Case Weight	0.5Kg	
ITF Outer Code	n/a	