

RS002/ALI/G2/AB
Heavy Duty Roller Shutter



- High Quality Alloy Finish
- Pre-resistored (A,B)
- Other resistor value available
- 45cm & 1m Armoured cable lengths
- EN50131-2-6 Grade 2
- Environmental Class III



Specifications

RS002 Grade 2

| | | | |
|------------------------------|-----------------------------|----------------------------|---------------------|
| <i>Connections</i> | 8 Core x 7/0.2 Copper Cable | <i>Voltage Range</i> | 12Vdc |
| <i>Armoured Cable Length</i> | 450mm | <i>Switching Current</i> | 500mA @ 12Vdc |
| <i>Reed Switches</i> | 1 | <i>Contact Material</i> | Rhodium |
| <i>Pull-in Gap</i> | 50mm | <i>Colours</i> | Aluminium |
| <i>Material</i> | Aluminium | <i>Tamper</i> | Integrity Loop |
| <i>Contact Size</i> | 175 x 50 x 13mm | <i>Standards</i> | EN50131-2-6 Grade 2 |
| <i>Magnet Size</i> | 85 x 70 x 30mm | <i>Environmental Class</i> | III |
| <i>Contact Form</i> | SPST form A | | |



Contact us:

Phone:

Tel: +44(0)151 6061000
 Fax: +44(0)151 6061122

Online:

Web: www.cqr.co.uk
 Email: info@cqr.co.uk

Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

