



Independently Certified
to EN50131

1 Grade 1



2 Grade 2

3 Grade 3

FIRE & SECURITY

GRADE 3 CONTACTS


SC517 MULTI SC517/WH or BR/MULTI/G3

- 65 x 13.5 x 13mm
- 4 Terminals
- Selectable Resistors (A, B, D, E, I)
- Microswitch Tamper
- Can be fitted in Normal Double Pole Configuration
- Can be used on Double Doors
- Available White or Brown
- Operating Gap - 10mm
- Magnetic Detection

3

SC570 MULTI SC570/WH or BR/MD/MULTI/G3



- 85 x 25 x 20mm
- 6 Terminals
- Selectable Resistors (A, B, D, E, F, H, I)
- Microswitch and Wall Tamper
- Operating Gap - 10mm
- Magnetic Detection

3

SC513 SC513/WH or BR/AC/G3





SC513/WH or BR/AC

- 65 x 13.5 x 13mm
- Pre-wired
- Operating Gap - 10mm
- Pre-resistor - see resistor guide for type
- Magnetic Detection

3



FC508 MULTI FC508/WH or BR/MULTI/G3

- Body 20(dia) x 30mm, Face Plate 22 x 33mm
- 4 Terminals
- Selectable Resistors (A, B, D, E, I)
- Microswitch Tamper
- Can be fitted in Normal Double Pole Configuration
- Can be used on Double Doors
- Operating Gap 6mm
- Magnetic Immunity

3

SC570 SC570/WH or BR/MD/G3

- 85 x 25 x 20mm
- 6 Terminals
- Cover and Wall Tamper
- Operating Gap - 10mm
- Magnetic Detection
- EN50131-2-6 Grade 3 Environmental Class II

3

GP001 GP001/AB/G3



- Heavy Duty Angled Aluminium Contact
- Operating Gap: 20 mm
- Size: 80 x 15 x 27 mm
- High Quality Alloy Finish
- Pre-restored (A, B)
- 57cm Armoured Cable Lengths
- Magnetic Detection
- Other resistor value available - see resistor guide for type

3

RS007 RS007/G3/AB



- Heavy Duty Roller Shutter
- Operating Gap: 20 mm
- Size: 175 x 50 x 15 mm
- High Quality Alloy Finish
- Selectable (A, B)
- Optional Floor Tamper
- Locating Mechanism to Aid Alignment
- 45cm & 1m Armoured Cable Lengths
- Other resistor value available - see resistor guide for type

3

Resistor Table Guide

Type	Resistor Guide	Switch	Tamper
A	Honeywell, Microtech (Galaxy)	1K Ohms	1K Ohms
B	Scantronic, Cooper, Pyronix PCX, Texecom, Castle-Care Tec G3+	4K7 Ohms	2K2 Ohms
C	Guardall (Network 1 configuration) Two wire only	8K2 Ohms	8K2 Ohms
D	DSC	5K6 Ohms	5K6 Ohms
E	Gardtec	6K8 Ohms	4K7 Ohms

Type	Resistor Guide	Switch	Tamper
F	Bosch, DA Abacus	8K2 Ohms	3K9 Ohms
G	Castle Care-Tec	13K Ohms	1K Ohms
H	Europlex, MDT	2K2 Ohms	2K2 Ohms
I	Pyronix Matrix, GE / Aritech, HKC	4K7 Ohms	4K7 Ohms
J	Texecom	22K Ohms	10K Ohms



FireBrand

2Y-LINK



CQR Fire & Security

125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

Sales: 0151 606 1000 Tech: 0151 606 6311 www.cqr.co.uk

info@cqr.co.uk

