

## **003:RSI SPECIFICATION SHEET**

**DET 0001 Water Sensor** 

#### **DET 0002 Glassbreak Detector**

#### **DET 0003 Fire Call Point**

RS



# **RSI IUT200 ACCESSORIES**

#### T. Sales

+44 (0)115 714 9990 +44 (0)1623 541 411

#### Technical

+44 (0)115 714 9999 +44 (0)1623 549 999

E. sales@vdomain.co.uk

W. www.vdomain.co.uk www.webeyecms.com

#### Additional products working into the RSI IUT200

These devices work through the IUT Internal transmitter allowing the Videofied<sup>®</sup> system to monitor flood, fire and glass breakages.



# 003:RSI SPECIFICATION SHEET

## **DET0001 Water Sensor**

the DET0001 is designed to allow water or any conductive non-flammable liquid to be detected with low voltage and low current. It can monitor up to two sensor probes simultaneously. Ideal for basements, laundry rooms and kitchen or anywhere flooding is a possibility and early warning is desirable to prevent damage.

Power	12 Volts DC	Relay Ra
Dimensions	Module size: 101mmW x 57mmH x 70D	Sensitivi
	Probe size: 51mmW x 25mmH x 13mmD	Alarm O

Relay Rating	5 amps
Sensitivity	two sensitivity setting for greater flexibility.
Alarm Output	SPDT Form C Relay Contact

## **DET0002 Glassbreak Detector**

The DET0002 Glassbreak Detector uses the latest technology to provide faster response and increased false alarm immunity. The DET0002 is specifically designed to allow fast, easy installation, while the adjustable sensitivity settings can compensate for the acoustics of any room and can be mounted on the ceiling, opposite wall, adjoining wall or the same wall as the glass.

Material	White high impact ABS plastic housing	Range	25" / 7.6m
Dimensions	(H x W x D) 98mm x 62mm x 21.8mm	Operating temperature	-10° /+50° C (+14° / +122° F)
Weight	90 g / 3.2 oz.		

## **DET0003 Fire Call Point**

To be used as a stand alone fire call point. Once activated it immediately sends an alarm via your Videofied system.

Material	PC/ABS	Colour	Red, Ral 3001
Dimensions	(H x W x D) 92mm x 90mm x 58mm	Operating temperature	-10° /+55° C (+14° / +131° F)
Weight	130g Flush 180g Surface		

T. Sales +44 (0)115 714 9990 +44 (0)1623 541 411

Technical +44 (0)115 714 9999 +44 (0)1623 549 999

E. sales@vdomain.co.uk

W. www.vdomain.co.uk www.webeyecms.com









