RAPIER



ELMDENE

Security & Fire Products

Benefits:

Superior quality metal External Sounder Ideal for prestigious installations and projects

Meets requirements for High Security installations (BS 7042)

Vandalism protected

Internal protection for long life in harsh environments

'Engineer Friendly' for easy installation and maintenance

Individual Cover logo can be supplied

Features:


- STAINLESS STEEL COVER
- POLISHED MIRROR FINISH AVAILABLE
- DUAL STEEL SKIN ENCLOSURE
- TWIN STREAMLINED TRANSLUCENT STROBES
- DUAL PIEZO SOUNDERS
- TWIN COMFORT LEDs
- ELECTRONICS FULLY ENCLOSED
- 15 MINUTE CUT-OFF TIMER
- FULL SAB FACILITY WITH ON-BOARD 12V NICAD BATTERY
- ENGINEER MODE FOR SILENT START-UP
- UNIVERSAL TRIGGER AND TAMPER
- HIGH SECURITY MODEL AVAILABLE (BS7042)
- HIGH SECURITY MODEL WITH SPEECH MODULE AVAILABLE
- SCREEN PRINTING AVAILABLE

External Sounders you can rely on





www.elmdene.co.uk



RAPIER

Specifications

Dimensions 340mm x 220mm x 55mm

Materials:

Cover Plated Painted or Stainless Steel (1.2mm)

Backplate Plated Steel (1.2mm)

Steel Protective Treatment Zinc Plated and Colour Passivated

Siren:

Input Voltage12V dc NominalOperating Voltage13.8V NominalCurrent350mA NominalSound Output118dB at 1m

Strobe:

Input Voltage 12V dc Nominal
Flash Rate 1 per Second
Current 150mA Nominal
Full SAB 12V NiCad Battery

Model	Cover	Cut-Off Timer	Drill Detectio	on Speech Module	Engineer Test Link
4000	White painted	Yes (15 min)	No	No	Yes (5 sec)
6000	'Mirror Finish'	Yes (15 min)	No	No	Yes (5 sec)
	Stainless Steel				
2000	'Mirror Finish'	Yes (15 min)	Yes	No	Yes (5 sec)
	Stainless Steel				
2000S	'Mirror Finish'	Yes (15 min)	Yes	Yes (with separate trigger	Yes (5 sec)
	Stainless Steel				

Speech module on 2000S pre-programmed messages

2000 and 2000S

standards (BS 7042)

Engineer Mode (On all Models)

Facility for announcing via on-board Speaker

Meet High Security

Silent start-up for installation

and maintenance

ELMDENE INTERNATIONAL LIMITED

Rodney Road, Fratton, Portsmouth PO4 8SS United Kingdom Tel: +44 (0)23 9273 9412 Fax: +44 (0)23 9281 1631

e-mail: sales@elmdene.co.uk

