

## **Technical Specification**

Product Code: SC2821PRO4

**Description:** Standard Bluetooth 2 Module 2 Channel, 7 day Timer, 100 Operations





**General Information** 

**Dimensions** 90mm x 36mm x 63mm

Display LCD Display
Wire Gauge 0.5 - 2.5mm²
Time Base Quartz Crystal

Quartz Crystal Accuracy (at  $\leq \pm 0.5$  Seconds/Day

20°C)

Warranty 3 Years

Power

Battery Type Replaceable CR2032

regulations

Construction

Material Self-Extinguishing Thermoplastic
Fixing Surface Mounting or DIN
Distribution Board 35mm DIN-rail (DIN EN 60715)

Mounting
Module Size 2

**Outputs** 

Contact Type 2 x SPDT

Total Switch Rating 16A @ 1.0pf, 230VAC
Min Switching power 1000 mW (10V/10mA)

Maximum Current Rating 10A @ 0.6pf (Inductive)

Outputs

Halogen, Filament Lamp 3000W Fluorescent Lamp 2600W

(Uncompensated)

Fluorescent Lamp (Series 2600W

compensated)

Fluorescent Lamp (Parallel 1300W

Compensated)

Compact Fluorescent Lamp 600W

**LED 230VAC** 600W

**Programming** 

**Programming Schedule** 24 Hour, and 7 Day Programmable

Available Operations 100 Operations

Switching Modes ON, OFF, Pulse, Extra, Permanent

Summer/Winter Time Yes; Automatic

Change

Pulse length - Pulse 00:01 up to 59.59 mm:ss

function (switching time)

Pulse length - Timer (man. 0:00:01 up to 9:59:59 h:mm:ss

switching)

Environment

Ingress Protection IP20 (DIN EN 60529)
Operating Temperature -30°C to 55°C

Accessories

143602 Module Enclosure

RHDC36FBG Grey 3.6mm Lens Full HD Camera
RHDC36FDW White 3.6mm Lens Full HD Camera
RHDC36FDG Grey 3.6mm Lens Full HD Camera

**Features** 

Daily and Weekly programming Switching capacity 16A per channel Zero-crossing, LED up to 600W Programmable via App (iOS and Android) 10 years battery reserve

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com

