## 



# Product Code: SHDV4KD2W2TB

Description:



#### 4 Channel Full HD 2TB DVR

System	
Operating System	Embedded LINUX
Main Processor	Embedded Processor
Video & Audio	
Video Input	SHDV4KD - 4 channel BNC SHDV8KD - 8 channel BNC
Audio Input	SHDV4KD - 4 channel RCA SHDV4KD - 4 channel RCA SHDV8KD - 4 channel RCA
Audio Output	1 channel RCA
Display	
Video Output	1 x HDMI, 1 x VGA, 1 x Auxiliary
Display Split	SHDV4KD - 1 and 4
	SHDV8KD - 1, 4 and 10
Resolution	1024×768, 1280×720, 1280×1024, 1440×900, 1920×1080, 2560x1440
Recording	,
Video/Audio Compression	H.264 Mainprofile/G.711A
Resolution	4 Megapixel
Record Rate (Main Stream)	SHDV4KD - 4ch 4MP recording SHDV8KD - 8ch 4MP recording
Recording Mode	Manual/Motion Detection/Schedule
Playback & Backup	
Sync Playback	SHDV4KD - 4ch 4MP recording SHDV8KD - 8ch 4MP recording
Backup Mode	Network/USB2.0 devices
Network	
Ethernet	RJ45 10M/100M
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
Network Monitoring	Web browsers, CMS, Android & iPhone apps
Storage	
Internal HDD	1 SATA HDD, up to 8TB per HDD
Auxiliary Interface	
USB Interface	2
General	
Power Consumption	<10W (without hard disk)
Operation Condition	0°C to +55°C / 10% – 90%
Dimensions	250mm x 230mm x 45mm
Power	
Operating Voltage	12V DC

### 3.6mm Lens 4MP HD Dome Camera - White

Sensor Size	1/3"	
Lens	3.6mm Fixed Lens	
Viewing Angle	76°	
Effective Pixels	4MP (2688 x 1520)	
Ingress Protection	IP66	
Minimum Illumination	0.1 Lux	
Auto Electronic Shutter	$1/50 \sim 1/100000 s$	
IR Distance	25 Metres	
Interface	BNC	
Power	12V	
Consumption	220mA	
Dimension	Ø114mm x 83 mm	
Weight	350g	
Storage Temperature	-30°C to +60°C	
Operating Temperature	-30°C to +50°C	
System Power Supply & Power Lead		
Software CD		
Manual		
HDMI Lead		
Mouse Control		
Remote Control (Batteries Included)		

#### Accessories

SHDVC36FBG 4MP 3.6mm Fixed Lens Bullet Camera, available in Grey & White

