



**SK9000U**

## **SIMPLEKEY BASIC MODULE, ULTRA**



SimpleKey Basic access control module for Ultra entrance panel, compatible with all systems. Equipped with RFID reader for activation of an opening using keys or Comelit cards. Can store up to 1500 electronic keys. Anodised aluminium alloy coating. Dimensions: 1 Ultra module. Dimensions: 100x90x35 mm

### **AWARDS**

DESIGN  
MILANO



**SK9000U**

**SIMPLEKEY BASIC MODULE, ULTRA**

**GENERAL DATA**

Height (inch) (in)	3.54
Width (inch) (in)	3.94
Depth (inch) (in)	1.38
Operating temperature (°F) (°F)	-13 ÷ 131
IP protection rating	IP65
Product color	Aluminium, Black RAL9005
Type of finishing materials	PMMA, Anodized aluminum
Removable terminals	Yes
Number of outputs (n°)	1
Product weight (oz) (oz)	12.35
Wall-mounted	Yes, with a dedicated accessory
Maximum absorption (W)	7.2
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Number of inputs (n°)	1
Operating humidity (RH max) (%)	25 ÷ 95
Door opener	Yes
Type of power supply	External power supply
Absorption in stand-by (W)	1.6
Number of auxiliary relays (n°)	1
Number of storable proximity keys	1500