



A mains powered, inter-connectable Carbon Monoxide alarm with battery back-up.

220V-240V

9V BATTERY BACK-UP


5 YEAR GUARANTEE

Application

- Commercial
- Industrial
- Residential

Specification

- Voltage:** 220-240V 50Hz
- Battery Back-up:** 9V Alkaline battery PP3 (Gold peak 1604A, Duracell MN1604, Energizer 522, IEC 6LR61, IEC6LF22)
- Battery Back-up Life Expectancy:** In the event of a break in the mains supply the battery will give detector operation for one year.
- Operation Current:** <35mA operation (in alarm)
- Type of Gas sensed:** Carbon Monoxide
- Sensor Life:** Ten years
- Guarantee:** Five years
- Alarm Reponse Time:** 50 PPM (Between 60 to 90 min) 100 PPM (Between 10 to 40 minutes) 300 PPM (Less than 3 minutes)
- Operation Temp.:** -10°C - 40°C
- Ambient Humidity:** 10%-90%
- Horn Level:** 85 Decibels at 1m
- Interconnectivity:**
- Facility:** 40 Detectors over 150 metres maximum
- Extra Info:** Certified to BS EN 50291-2010+A1:2012 & KM 651575



BS
EN 50291-
2010+A1:2012
LICENSE NO:
KM 651575

MODEL	VOLTAGE	TYPE	DIMENSIONS (L X W X D MM)
SMAC-3	220-240V	CO SENSOR	130 x 75 x 46mm