

# PICCOLO

## INTERNAL SOUNDER

This remotely powered sounder features a piezo sounder and two bright LED's for audible and visual indication. The sound output is selectable for either alternating or continuous tone. It is also protected against tampering by means of lid removal and removal from the mounting surface.



- Low profile design
- 115dB Sound output
- Selectable alternating or continuous tone
- Flashing alarm indication
- Low current consumption
- Tamper protected lid and mounting



### Specifications

Nominal Power Supply: 12v DC

Voltage Range: 9-15v DC

Sounder Type: Piezo

Sound Output Level: 115dB(A) @ 1 Metre

Sound Only Current: 84mA @ 12v DC

Flash Only Current: 17mA @ 12v DC

Sound and Flash: 100mA @ 12v DC

Operating Temp: -15°C to +40°C

Material: Polycarbonate

Dimensions: 125mm x 85mm x 37.5mm

Product Code: SO/PICCOLO/BL or RD



Contact us:

Phone:

Tel: +44(0)151 6061000

Fax: +44(0)151 6061122

Online:

Web: [www.cqr.co.uk](http://www.cqr.co.uk)

Email: [info@cqr.co.uk](mailto:info@cqr.co.uk)



Address: CQR Fire & Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK.

