



# SSIP2B

## H.264 2MP Starvis IP Stainless Steel IR Bullet Camera

*The SSIP2B is a 2MP (1080p) High Definition 12v DC/ POE IP Stainless Steel Bullet camera using the latest Starvis image sensor. The body is a 316 grade Stainless Steel, a ideal choice for Coastal Applications.*



SSIP2B

### Key Features

- 1/28" Sony 2MP Starvis Image Sensor
- 1080P Full HD Resolution
- 3.6mm Megapixel Fixed Lens
- ONVIF Profile S Compliant
- Triple Codec (H.264/MPEG4/MJPEG)
- True Day & Night with ICR mechanism
- D-WDR (Digital Wide Dynamic Range)
- 3DNR (Digital Noise Reduction)
- 12v DC/ POE Operation
- 316 Grade Stainless Steel Housing
- IP 67 Rating

### Accessories



## Technical Specification

Model Number	SSIP2B
Image Sensor	Sony 2MP Starvis Image Sensor
Size	1/2.8 Inch
Lens	3.6mm Fixed Lens
Scan Systems	Progressive Scan
Total Pixels	2000(H) x 1121 (V), 2.24 Mega Pixels
Effective Pixels	1984(H) x 1105(V), 2.19 Mega Pixels
Day & Night	Auto/ Day (Color)/ Night (BW), ICR Control
Privacy Area	On/Off (6 Programmable Zone)
Motion Detection	48 Zone, Sensitivity 1~5 Step, On/Off
LPR	Auto 1/15 - 1/1900, On/Off
WDR	DWDR (1-5 Step) On/Off
3DNR	Digital Noise Reduction 1-63 Step
Elec. Shutter	Auto (1/15-1/15000), Suppress Rolling, Manual
Color Adjust	Bright/Contrast/Saturation/ Sharp/ Hue
White Balance	Auto/Indoor/Outdoor/Fluorescent
OSD Display	Text, Data, Time, Event, On/Off
Image Mirror	Normal/Mirror (H)/ flip (V)/ Both (HV)
Power Supply	DC12V +/- 10%
Operating Temp	-10°C +50°C
Preservation Temp	-10°C +60°C
Humidity	0%-90%
Dimensions/mm	78 (D) x 158.5 (W) x120 (H)
IP Rating	IP67
Weight (Kg)	1.52 (Approx.)

Genie Access reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

## Dimensions (mm)

