

SW-PSU 1A/12V



1 Amp, 12 Volt Power Supply

The **SW-PSU1A/12V** power supply is designed to the EN 50131-6 standard and delivers 1A at a nominal 12Vdc. It can be installed either as standalone units or wired to HKC **SecureWatch** and **SecureWave** panels via an ID sensor bus.

- Delivers 1A total current
- 5 PSUs per ID bus (20 in total)
- 2 programmable changeover relay outputs
- Fuse monitoring
- Automatic battery test
- 1.2mm steel box with hinged door
- Battery current monitoring
- Mains fail detect
- Deep discharge protection
- Programmable User descriptions
- System overview facility
- Mains: 230Vac +10% -15%, 50Hz
- Output: 13.7Vdc + 5% -10%
Max. ripple: 300mV peak to peak
- Current Consumption: 75mA @ 12Vdc (relays off)
Max. = 145mA @ 12Vdc (all relays on)
- Temperature: -10 to +40 °C
- Weight: 3,100g
- Size: 236mm x 360mm x 86mm
- EN 50131-6 Grade 2, Class II



SecureWatch

SecureWave
868MHz Radio

www.hkcsecurity.com

Thank you for considering HKC products for your security system.

For further information in relation to any of our products, please contact us at:

HKC Ltd.
Parkway Business Centre,
Ballymount,
Dublin 24, Ireland.
T: 353 1 456 7007
F: 353 1 456 8332
E: sales@hkc.ie

HKC Ltd.
James Hill Street,
Littleborough,
Lancashire.
OL12 0HA
T: 44 1706 373560
F: 44 1706 378460

or visit us at www.hkcsecurity.com

UK Technical Support: 01706 838746 or 0800 111 4599

Safe & Secure