

Slimline Door Contact



A wireless slimline door contact for detecting threats and alerting system users. Keeping property, people and belongings safe.

With a choice of 3 different finishes to suit all installations.

At a glance...

- Grade 2 radio product
- 3 years battery life using a CR2 battery
- Flexible installation options
- Independently certified to EN50131 and INCERT
- Sleek and compact design

Product specification

Certified for EN05131 & INCERT	
Battery type:	CR2 3V Lithium
Typical battery life:	3 years
Max operating temperature	55 °C
Wireless frequency:	868.6625MHz
Grade:	2
Door contact dimensions:	103mm 19mm, 24mm (LxWxH)
Environmental class:	II
Weight with CR2 cell installed	40g
Weight of magnet holder	10g

Compatible products

i-on30R	30 zone radio control panel
i-on40H	40 zone hybrid control panel
Compact	20 zone integrated panel and keypad
Style	40 zone integrated panel and keypad
768 & 769	8-32 channel narrow band receivers
EXP-R10	10 zone radio expander
EXP-R30	30 zone radio expander
i-on30EX/ EXEUR	30 zone control panel
i-on50EX/ EXEUR	50 zone control panel
i-on160EX/ EXEUR	160 zone control panel
Multibus	1000 zone control panel
Menvier30KPZ	30 zone control panel
Menvier40KPZ	40 zone control panel
Menvier100KPZ	100 zone control panel
Menvier300KPZ	300 zone control panel
Eaton legacy panels & legacy radio expanders 868MHz	