



	IPGUARD MINI	IPGUARD MINI PLUS
REFERENCES	TP4G-A	TP4G-I
MECHANICAL CHARACTERISTICS		
Facia dimensions (HxWxD)	270 x 120 x 14 mm	280 x 120 x 3 mm
Backbox dimensions (HxWxD)	245 x 95 x 45 mm	254 x 95 x 60 mm
Weight	1200 g	1200 g
Material	Aluminium	Stainless Steel 316 / Brass
Finish	Brushed	
Protection rating	IK09 / IP54	
ELECTRICAL CHARACTERISTICS		
Power	12 V DC	
Consumption	2A max (whilst communicating via 4G)	
Relay	2no 5 Amp rated NO/NC programmable	
Temperature	Operating -25°C to 70°C / Storage -40°C to 85°C	
FEATURES		
Colour camera	Pinhole hidden, angle of view H 60°, V 45°	
Screen	TFT colour 2.9"	
Proximity reader	Anti-vandal makrolon, illuminated	
Keypad	Large 15.6mm dia raised illuminated buttons, braille embossed	
Capacity	3000 names / flats	
Inputs	2 no	
Smartphone App	IPGUARD APP on Google Play (Android), App Store (APPLE)	
Programming	WWW.BATICONNECT.COM available 24/7/365 real time	
Standard features	Customisable welcome screen – Backlight compensation – Proximity key & radio transmitter ANTI-CLONE guarantee – Smartphone access	
Mobile access	Open door via app on smart devices from anywhere, at any time	
Advanced features		Hearing aid loop

Find out more about our smart door entry and access control solutions by visiting www.ipdoentry.co.uk

Take back control of your property

08000 156496
 sales@ipdoentry.co.uk
 www.ipdoentry.co.uk
 f ipdoentry

IP Door Entry Limited
 Unit DC4 Prologis Park
 Eastman Way
 Hemel Hempstead
 HP2 7DU



IPGUARD
4G/IP SMART
 Visitor Door Entry

