

TX-2214-03-1

Wireless PIR 16m 868AM Gen2

One way transmitter

The sensor has a chip tuned wireless transmitter that communicates with a 868AM Gen2 receiver as, for example the ATS1235.

The learn-in process of the sensor is identical to the process used with legacy sensors.

Each sensor reports a unique ID code with each transmission.

The sensor also reports the battery and transmitter condition (supervisory signal) to the panel every 18 minutes.

Mirror power

The patented optical mirror technology gives the advantage of gliding focus, which creates a volumetric detection curtain from floor level up to installation height resulting in a sensor that never loses track of the object.

In these series we are using a dual element digital pyro generating two volumetric curtains for each of the nine curtain sets.

5D signal processing

The unique 5D signal processing technology will look for a match in shape, size, speed, duration and environment to decide on an alarm condition.

The result is a unique combination of high detection sensitivity with high false alarm immunity.

Ease and flexibility of installation

1. Easy opening and closing system.
2. Easy access when changing the batteries.
3. Easy access to the mirror optics.
4. Tolerates wall angle deviation and different mounting heights.
5. Limited loss of coverage when objects are placed in the field of the PIR vision.
6. One mounting plate for all sensors in the series.

Other members of the family

This family includes motion sensors with variants in detection ranges and a Pet Immune variant.

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.



Details

- Proven mirror optics inside to get a dense coverage pattern
- Selectable coverage pattern using mirror masks
- Full under crawl detection
- "5D" signal processing for false alarm immunity
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 5-years battery life with 1 battery
- Holding several security approvals

TX-2214-03-1

Wireless PIR 16m 868AM Gen2

Technical specifications

General

Technology	PIR
Application type	Surface Mount
Anti masking	No
Pet immune	No
Camera	No
Pry-off tamper kit	On board
Detector start-up time	1 min

Detection

Detection range selection	10 or 16m
Coverage (field of view)	86°
Undercrawl protection	Yes
No. of curtains	9
Target speed range	0.3 m/s to 3 m/s

Wired/wireless

Wired-wireless	Wireless
Wireless frequency	868 MHz AM

Electrical

Current consumption	22 µA (avg.), 50 mA (max.)
Batteries	1 x CR123A (3.0 V, 1300 mAh lithium)
Battery lifetime	5 years

Physical

Physical dimensions	130 x 69 x 53
Net weight	146 g
Mounting height	1.8 to 3 m

Environmental

Operating temperature	-10° to +55° C
Relative humidity	95% max. noncondensing
Environment	Indoor
IP rating	IP30 IK02

Standards & regulation

EN50131 grade	Grade 2
Certification	INCERT

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

