



1622

IKALL SIMPLEBUS AUDIO SPEAKER



Audio speaker unit complete with terminal block and digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP switch with 8 positions for programming user calls. 33Vdc from power supply unit part. 1595. On-board electronic lock-release function (3A), plus a 10A relay. Timed lock-release inputs and door open indication.. For use in modules part. 33400, 33401 and 33402. Compatible with all SBTOP functions and products. Dimensions: 102x55x38 mm.



1622

IKALL SIMPLEBUS AUDIO SPEAKER

MAIN FEATURES

Audio system:	Yes
Audio system:	Yes
Audio/video system:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131

FUNCTIONS

Key button function:	Yes
----------------------	-----

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA

Product height (inch):	2.17
Product width (inch):	4.02
Product depth (inch):	1.5

COMPATIBILITY

Simplebus 1 audio system:	Yes
---------------------------	-----

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes