



1622L

SIMPLEBUS AUDIO UNIT WITH LED, IKALL SERIES



Audio speaker unit for Simplebus system complete with terminal block and digital audio control system with echo-cancelling, sealed-unit loudspeaker, electret microphone and front-mounted loudspeaker volume control. Complete with microprocessor and 8-position dip switch for programming user calls. Programmable audiovisual functions for users with disabilities. 33 Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A) plus a 10A relay. Timed lock-release inputs and door open indication. Dimensions: 102x55x38 mm.



1622L

SIMPLEBUS AUDIO UNIT WITH LED, IKALL SERIES

MAIN FEATURES

Audio system:	Yes
Audio system:	Yes
Audio/video system:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131

FUNCTIONS

Key button function:	Yes
----------------------	-----

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes
Speech synthesis:	Yes

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA

Product height (inch):	2.17
Product width (inch):	4.02
Product depth (inch):	1.5

COMPATIBILITY

Simplebus Top audio/video system:	Yes
Simplebus 1 audio system:	Yes

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes