« Comelif



2619

SIMPLEBUS TOP STYLE INTERCOM HANDSET





Entry phone with electronic call, conversation button on base, call volume control, privacy function, and conversation privacy. Equipped with a series of key buttons and a further 8 buttons for intercom function or various services (2 of the buttons can be used as a C/N.O contact). Equipped with LED that may be used for various signals (busy, doctor function). Complete with 8-position dip switch for selection of the desired user code. Door entry phone for use in all Simplebus systems. Allows management of floor door call, call repeat, sending of alarm signals to the porter switchboard, call to main switchboard, secondary switchboard and guardian door entry-phone. Allows direct intercom calls between users with the use of an interface or porter switchboard and the use of a number of relay actuators; programming of buttons does not require dedicated programmers. Fitted with terminal art. 1214/2C. The fascia can be changed on this model. Dimensions: 95x215x58 mm.



SIMPLEBUS TOP STYLE INTERCOM HANDSET

MAIN FEATURES		
Audio system:	Yes	
Audio/video system:	No	
Flush-mounted:	No	
Wall-mounted:	Yes	
Desk base-mounted:	Yes	
Hands-free function:	No	
Induction loop function:	No	
Product colour:	White RAL9003, cover light blue	
Interchangeable cover:	Yes	
Sensitive Touch technology:	No	
Total buttons:	9	
LED signaling (no.):	1	

FUNCTIONS

Actuator control function:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Call to group addresses:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Doctor:	Yes
Redial:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Mechanical ringtone:	No
Customisable ringtone:	Yes
Alarm function:	No
Privacy conversation function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Customisable housing:	Yes
SETTINGS	
Loudspeaker volume control:	Yes



SIMPLEBUS TOP STYLE INTERCOM HANDSET

SETTINGS	
Microphone volume control:	Yes
Ringtone volume control:	Yes
GENERAL DATA	

Product height (inch):	8.46
Product width (inch):	3.74
Product depth (inch):	2.28

COMPATIBILITY

TECHNICAL CHARACTERISTICS	
Power supply voltage:	22 ÷ 28
Minimum current absorption (mA):	1
Maximum current absorption (mA):	200
Microphone:	9,6x6,9mm omni-direction
Loudspeaker:	
IP protection rating:	IP30
Operating temperature (°F):	23 ÷ 104
Product weight (oz):	0
Clamps:	L L CFP CFP LED+LED- SS+C8 P8 C9 P9



SIMPLEBUS TOP STYLE INTERCOM HANDSET

CCESSORIES		
	1214/2C	VIDEO FILTER FOR SIMPLEBUS COLOUR SYSTEM Line branch terminal for colour monitors. The terminal must be connected on the riser to be branched towar brackets or telephones.
* *	1626	STYLE ADDITIONAL PUSH BUTTON Pushbutton to be inserted in the base of the Style Elegance handsets.
	1627	LED FOR STYLE ELEGANCE H/SET Blue LED to be inserted in the base of the Style Elegance handsets. 12-24V AC-DC operation.
	1627B	ACCESSORY - 1 ADDITIONAL LED FOR STYLE INTERCOM - BLACK Blue LED to be inserted in the base of the telephone. Takes up the space of one element. 12-24V AC-I operation.
	2600/1	PALE BLUE FACIA FOR STYLE ELEGANCE Pale blue facia for Style elegance version telephone
	2600/2	GREEN FACIA FOR STYLE ELEGANCE Green facia for Style elegance version telephone

The technical specifications are subject to variations without warning.



SIMPLEBUS TOP STYLE INTERCOM HANDSET

ACCESSORIES		
	2600/3	BLACK FACIA FOR STYLE ELEGANCE Black facia for Style elegance version telephone
	2600/4	ORANGE FACIA FOR STYLE ELEGANCE Orange facia for Style elegance version telephone
	2600/5	RED COVER ACCESSORY FOR STYLE ELEGANCE DOOR ENTRY PHONE Red facia for Style elegance version telephone
	2642W/16	WHITE DESK BASE FOR STYLE 16 WIRE White desk conversion kit for Style series handsets. Complete with 1.5 mt of white cable and connection fitted with 16 connection terminals. Dimensions 84X189X32 mm.
	2642W/28	WHITE DESK BASE FOR STYLE 28 WIRE White desk conversion kit for Style series handsets. Complete with 1.5 mt of white cable and connection fitted with 28 connection terminals. Dimensions 84X189X32 mm.