

3360B

« Comelit



Digital call module with 128x64 dot graphic LCD display and keypad with 21 buttons backlit with blue LEDs. Also functions as an electronic key code. Two search buttons are used to scroll though the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. For the SBC system (factory setting), the electronic name directory saves up to 3500 user names and 6000 lock-release passwords. Users and settings are simple to program using PC software art. 1249B (included, with USB connection cable) via a USB or RS485 port, or locally on the digital module itself. Includes the CD-ROM loaded with serial download SW art. 1249B for installation to PC and the USB connection cable. Dimensions: 112x180x40

3360B

2-WIRE AND VIP CALL MODULE. IKALL SERIES

MAIN FEATURES	
Product height (inch):	7.09
Product width (inch):	4.41
Product depth (inch):	1.57
Operating temperature (°F):	-13 ÷ 131
RH max operating humidity (%):	25 ÷ 75
Maximum current absorption (mA):	80

SOFTWARE/FIRMWARE SPECIFICATIONS	
No. of storable users:	3500

FUNCTIONS	
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Total buttons:	18

GENERAL DATA	
Product colour:	Black RAL9005

COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Building Kit audio/video system:	Yes
Simplebus 2 audio system:	Yes
Vip system:	Yes

MOUNTING/INSTALLATION	
Flush-mounted:	Yes
Wall-mounted:	Yes

AUDIO/VIDEO FEATURES	
Display size (inch):	3
Display resolution HxV (inch):	128x64 dots
Type of display:	Alphanumeric

CONNECTIVITY	
Type of connections/ports:	RS485, USB



3360B

2-WIRE AND VIP CALL MODULE. IKALL SERIES

CONNECTIVITY	
RS485 ports:	1