



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE, SIMPLEBUS2 AUDIO

«Comeliť			
	Ci		
C-•		85	

Mini series door-entry phone with full-duplex audio. Allows loudspeaker volume control and ringtone volume control, with choice of different melodies. Equipped with 5 touch sensitive buttons for audio key, lock-release, actuator control, switchboard call and privacy function, with door status indicator LED. Manages floor door calls as standard. Complete with 2 x 8-position dip-switches for programming user code and buttons. Wall-mounted. The door-entry phone can be used in Simplebus2 audio systems with power supply art. 1210. Dimensions: 105x105x20 mm.



DOOR ENTRY SYSTEMS & KITS MINI HANDSET AUDIO



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE, SIMPLEBUS2 AUDIO

MAIN FEATURES		
Audio system:	No	
Audio/video system:	Yes	
Flush-mounted:	No	
Wall-mounted:	Yes	
Desk base-mounted:	Yes	
Hands-free function:	Yes	
Induction loop function:	Yes	
Touch screen display:	No	
Product colour:	White	
Sensitive Touch technology:	Yes	
Total buttons:	5	
LED signaling (no.):	3	
Wi-Fi Port:	No	
Comaptibility with Video Entry Comelit App:	No	

FUNCTIONS	
Actuator control function:	Yes
Switchboard call function:	Yes
Priority calls:	Yes
Intercom function:	Yes
Selective intercom call:	Yes
Call to multiple addresses:	Yes
Privacy function:	Yes
Doctor:	Yes
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Removable terminals:	Yes
Type of finish:	Plastic

SETTINGS	
Loudspeaker volume control:	Yes
Ringtone volume control:	Yes

GENERAL DATA	
Product height (mm):	104.9

The technical specifications are subject to variations without warning.

DOOR ENTRY SYSTEMS & KITS MINI HANDSET AUDIO



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE, SIMPLEBUS2 AUDIO

GENERAL DATA	
Product width (mm):	104.9
Product depth (mm):	20.07

COMPATIBILITY	
Simplebus 2 audio system:	Yes

TECHNICAL CHARACTERISTICS	
Power supply voltage (VDC):	22 ÷ 35
Absorption in stand-by (mA):	2
Absorption during communication (mA):	130
IP protection rating:	IP30
Operating temperature (°C):	-5 ÷ 40
RH max operating humidity (%):	25 ÷ 75
Product weight (g):	149.69
Clamps:	L L CFP1 CFP2

6754



6751W

HANDS-FREE MINI DOOR-ENTRY PHONE, SIMPLEBUS2 AUDIO

ACCESSORIES



Adapter plate for Mini Handsfree audio