





Colour monitor for flush-mounting (on Art. 6817) or wall-mounting (on support Art. 6820) with 7" 16:9 screen, hands-free full-duplex audio and touch sensitive controls. Allows brightness, contrast and audio volume control, plus adjustment of the volume of the ringtone, which can be customised with a choice of different melodies. Equipped as standard with control buttons for lock-release and audio enable/disable with relative indicator LEDs, plus 6 further buttons for self-ignition, privacy service and other programmable functions. Manages floor door calls and call repeat as standard. Complete with 2 x 8-position DIP-switches for user code programming and button programming. Equipped with riser distribution terminal Art 1214/2C. The monitor can only be used in 2-wire SimplebusTop Color systems. Dimensions: 223x124x25mm.

AWARDS







7-INCH MAXI MONITOR, SBTOP

MAIN FEATURES	
Audio system:	No
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Type of display:	LCD
Display size (inch):	7" 16:9
Touch screen display:	No
Display resolution HxV (inch):	800x480
B/W or colour display:	Color
Product colour:	White RAL9003
Sensitive Touch technology:	Yes
Total buttons:	14
LED signaling (no.):	14
Wi-Fi Port:	No
Comaptibility with Video Entry Comelit App:	No

FUNCTIONS	
Actuator control function:	Yes
Self-ignition:	Yes
Switchboard call function:	Yes
Intercom function:	Yes
Call forwarding:	Yes
Privacy function:	Yes
Redial:	Yes
Floor door call function:	Yes
Customisable ringtone:	Yes
Alarm function:	Yes
Sound diffusion control:	Yes
Receiving text messages:	Yes
Images reception:	Yes
Privacy conversation function:	Yes
Key button function:	Yes

HARDWARE SPECIFICATIONS	
Removable terminals:	Yes



7-INCH MAXI MONITOR, SBTOP

SETTINGS	
Loudspeaker volume control:	Yes
Microphone volume control:	Yes
Ringtone volume control:	Yes
Display brightness control:	Yes
Display contrast control:	Yes
Display colour control:	Yes

GENERAL DATA	
Product height (inch):	4.88
Product width (inch):	8.78
Product depth (inch):	0.98

COMPATIBILITY	
Simplebus Top audio/video system:	Yes
Building Kit audio/video system:	Yes
Kit audio/video system:	Yes

TECHNICAL CHARACTERISTICS	
Power supply voltage:	0 ÷ 28
Maximum current absorption (mA):	400
Absorption in stand-by (mA):	36.00
Absorption during call (mA):	310.00
Absorption during communication (mA):	400.00
Microphone:	5mm omni-direction
Loudspeaker:	80mm 800hm 1W
IP protection rating:	IP30
Operating temperature (°F):	104 ÷
RH max operating humidity (%):	0 ÷ 75
Product weight (oz):	0
Clamps:	CFP1 CFP2 IN1 IN2 S+S-



7-INCH MAXI MONITOR, SBTOP

ACCESSORIES

6817

FLUSH-MOUNTED BOX FOR MAXI MONITOR

Flush-mounted box in black ABS. Dimensions: 212x115x50mm



6820

SBC & VIP MAXI MONITOR WALL SUPPORT

Wall support for Maxi monitor. White. Dimensions: 216x117x16 mm.



6812

DESK BASE FOR MAXI MONITOR

Desk base for desktop conversion of Maxi monitor. Dimensions: 105x75x110 mm.