« Comelif





## 8461I

## SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM





2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893, 1 power supply unit art. 1209, 1 Mini series color monitor with handset art. 6601W, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.



6601W



## 8461I

## SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

KIT PRODUCT



### ICONA MONITOR, SBTOP

Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire SimplebusTop Colour systems. Dimensions 142.5x147x23 mm.

## MAIN FEATURES - 6601W

No
Yes
No
LCD
4,3" 16:9
No
480x272
Color
White RAL9003
Yes
9
No



#### QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

MAIN FEATURES - 4893M	
Туре:	Monoblock entrance panel
Material:	Die-cast aluminium
Audio/video system:	Yes

The technical specifications are subject to variations without warning.

4893M

## DOOR ENTRY SYSTEMS & KITS KIT VIDEO QUADRA



### 8461I

## SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

MAIN FEATURES - 4893M	
Wall-mounted:	Yes
Camera:	Colors
Type of sensor:	1/4" CMOS
Lens size (inch):	0.08
Diagonal viewing angle (°):	100
Minimum colour lighting (lux):	1
Power supply:	Bus
Maximum current absorption (mA):	250
Clamps:	LL RTE COM DO SE- SE+C NC NO
Buttons to call:	Yes
Total buttons:	4
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
IP protection rating:	IP54
Vandal Resistant rating (IK code):	IK08
Backlighting colour:	White

### 1216

6117

#### VIDEO RISER TERMINATION FOR SIMPLEBUS

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.



### PLANUX, SMART, ICONA FLUSH BACKBOX

Flush mounted box for Planux,Smart and Icona monitors Dimensions: 132x132x50mm

## MAIN FEATURES - 6117

Product height (inch):	5.2
Product width (inch):	5.2
Product depth (inch):	1.97



## SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

### KIT PRODUCT



6620

1209

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



### 2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one for external unit and one for the monitor power supply. Input voltage 110-240 VAC. Dimensions: 106 x 62 x 89 mm (6 DIN modules).

## Main Features - 1209

Alternating input voltage (VAC):	110÷240
Output voltage (VDC):	33
Input connector:	Terminal block
Applicable to DIN rail:	Yes
Number of DIN modules:	6
Max. current delivered (A):	1.20



# SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

ACCESSORIES		
•	4791	Adapter plate for Quadra Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm
	4792	RAIN SHIELD FOR QUADRA ENTRANCE PANEL Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.
	4793MB	BLACK FACEPLATE FOR QUADRA W/BUTTONS
	4793MC	CORTEN FACEPLATE FOR QUADRA W/BUTTONS Corten color faceplate for Quadra entrance panel with mechanical buttons.
	4793MA	ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS
	1217	NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL The kit contains 10 sheets of adhesive labels for nameplates

The technical specifications are subject to variations without warning.



# SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

ACCESSORIES		
Software	1235A	NAMEPLATE LABEL PRINTING SOFTWARE Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website
	6117	PLANUX, SMART, ICONA FLUSH BACKBOX Flush mounted box for Planux,Smart and Icona monitors Dimensions: 132x132x50mm
	6118	PLANUX CLIPS FOR DRY LINED WALLS Installation kit for plasterboard walls.
	6620	WALL BRACKET FOR ICONA MONITOR Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.
C 1+	6612	DESK BASE FOR ICONA MONITOR Adjustable tilt desk base converts the Icona monitor into a desktop version. Complete with 1 x 2 m labelled RJ45 cable for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 145x190x120 mm.
	1209	2-WIRE VIDEO KIT POWER SUPPLY UNIT 33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one for external unit and one for the monitor power supply. Input voltage 110-240 VAC. Dimensions: 106 x 62 x 89 mm (6 DIN modules).



# SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

ACCESSORIES		
	1229A	ADDITIONAL RINGTONE ACCESSORY FOR SIMPLEBUS2 SYSTEM Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24 mm.
	1256	ACTUATOR RELAY Intelligent Simplebus device for controlling a 12-24 V relay contact. If used in mixed audio/video systems, the actuator relay needs a video filter to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 66x85Xx35 mm (4 DIN modules).
	1404	DIGITAL SWITCHING DEVICE. 2-WIRE SYSTEM Audio/video switching module for Simplebus Top 2-wire digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).
	1405	DIGITAL EXCHANGE 2 QUADRA INPUTS. SBTOP Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).
	1409	ACCESSORY FOR REMOTE COLOUR CAMERAS, 2-WIRE SYSTEM Remote camera module for Simplebus Top 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).