

The WIP2BVL series are IP IR varifocal bullet cameras with a 2.8-12mm lens as well as a 20-30m IR distance in ideal conditions. The cameras both have 1080P full real time coding as well as remote monitoring and are available in white or grey finish.



Key Features

- 1080P Full real time coding
- 20-30m IR distance (In ideal conditions)
- 2.8-12mm megapixel lens
- 3D DNR
- Digital WDR
- True day / night
- MIC / Line in G.711A / U Audio Codec
- IP and MAC address filtering
- Configuration backup
- Alarm image size dependent on set stream resolution
- RTSP streaming with or without authentication
- Mirror and flip image
- Multiple privacy masking
- Remote monitoring
- Supports smart phones and tablets, P2P connectivity
- Available in white or grey

Accessories



WIPMPJB
White Multi Platform Junction Box



WIPMPJBG
Grey Multi Platform Junction Box



WIPJBBV
White Junction Box for Varifocal Cameras



WIPJBBVG
Grey Junction Box for Varifocal Cameras



Specification

Model Number	WIP2BVL	WIP2BVLG
Image Sensor	1/3" CMOS	
Image Pixels	1920 x 1080	
Effective Pixels (H x V)	752 x 582	
Electronic Shutter	1/25s ~ 1/100,000s	
Minimum Illumination	0 Lux (IR LED On)	
Lens	2.8 ~ 12mm	
Video Format	PAL / NTSC	
WDR	Yes	
3D DNR	Yes	
Video Compression	H.264	
Resolution	1080P (1920 x 1080), 720P (1280 x 720), VGA (640 x 480), QVGA (320 x 240)	
Multi-Stream	1920 x 1080 (1-30fps) / 1280 x 720 (1-30fps) 1280 x 720 (1-10fps) / 640 x 480 (1-30fps) / 320 x 240 (1-30fps)	
Bit Rate	64Kbps ~ 4Mbps	
Encode Mode	VBR / CBR	
Quality	Five levels under VBR, Freely adjustable under CBR	
Image Settings	Saturation, Brightness, Contrast, etc (Adjustable through client software or web browser)	
Audio Compression	G711A	
Network Interface	RJ45	
Audio Interface	One way audio (MIC in x1)	
Remote Monitoring	IE browsing, CMS remote control	
Online Connection	Support simultaneous monitoring for up to 4 Users Support multi-stream real time transmission	
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP	
Smart Alarm	Motion alarm	
Day & Night	ICR	
IR Distance	Up to 25m (In ideal conditions)	
IP Rating	IP66	
Power Supply	DC12V / PoE	
Operating Conditions	Temperature: -40°C ~ 50°C, Humidity: 10% ~ 90%	
Dimensions	Ø109 x 284 (L) mm	
Weight	1115g	

Genie Access reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Dimensions (mm)

