

▶ 17" LCD DISPLAY

X-17AV/X-17A



▶ FEATURES

- Distinctive aluminum alloy housing for added strength
- Fast 16ms response time
- NeoV Optical Filter™
- High 450 contrast ratio
- DVI ready for high quality signal
- S-Video* and CVBS* inputs
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount



▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264mm
	Brightness	400cd/m ² (Typical)
	Contrast Ratio	450:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	140°/140° (Typical)
	Display Color	16.7M
	Response Time	16ms
Input	Frequency (H/V)	H: 30kHz - 80kHz V: 50Hz - 75Hz
	Max. Pixel Clock	135MHz
	Life Time	40,000hrs (Minimum)
Connector	Analog	15-Pin D-Sub
	Digital	29-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
NeoV Optical Filter	Power	3-Pin AC Plug
	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
Tilt	Hardness	>6H (MOH's Rating)
	Tilt	0° ~ +15°
	VESA FPMPMI	Yes (100mm)
Regulation Approval	Safety & EMI	FCC, UL/CUL, EPA, CE, TUB/BAURT, NORDIC, CB GOST, BSMI, VCCI, TCO 95, ISO 13406-2
	VESA	DDC 1/2B, DPMS
	Power AC Consumption	100 - 240V, 50 - 60Hz <48W (On) <4W (Stand-by) <2W (Off)
	Dimensions	Net (W x H x D) 408 x 398 x 175mm (16.1" x 15.7" x 6.9") Packing (W x H x D) 495 x 510 x 228mm (19.5" x 20.0" x 9.0")
Weight	Net Weight	6.8Kg (13.9lbs)
	Gross Weight	9.5Kg (20.9lbs)
Packing	1 Pallet	40 Cartons
	20' Container	400 Sets
	40' Container	880 Sets

*Video function is only available on X-17AV

All specifications are subject to change without prior notice.