

Description

The XL GPRS alarm panel is a Videofied® wireless, battery operated security system. The control panel is designed for residential and small commercial security applications where video verification is needed or desired.

The control panel is powered by eight 1.5-volt alkaline batteries that last up to four years, with normal system activity. A built-in siren provides status beeps. The embedded cell modem communicator reports to the monitoring station and enables 2-way voice communication over cell to the monitoring station.

A dual-tamper function is active 24 hours, whether or not the system is armed. An alarm occurs if the control panel cover is removed, or if the control panel is removed from the mounting surface.

With the embedded touchpad the user can arm and disarm the system. Under the TouchPad an integrated proximity card reader that can be used to arm and disarm the system without using the TouchPad. The proximity card/tag arming system is designed to maximize operator convenience.

Features

- > S²View® : Spread Spectrum, Videofied, Interactive AES Encrypted Wireless technology provides optimum signal integrity and security.
- > Compatibility : works with all Videofied® wireless devices.
- > Supervision of all devices (except remote keyfob).
- > Tamper detection : 24-hour dual-tamper function provides detection for both cover and wall removal. Control panel also monitors all system device tamper switches.
- > Zones / Devices : 19 maximum.
- > Areas : 4 maximum. Area 1 predefined from factory for entry/exit delay. Areas 2, 3, and 4 can be configured as needed.



Supervised Wireless Technology

The XL series, along with all Videofied devices uses patented S²View® - Spread Spectrum, Videofied, Interactive, AES Encrypted Wireless technology, providing optimum signal integrity and security.

Bi-directional RF communication between all system devices and the system control panel assure high signal reliability.

Integrated antennas eliminate protruding wires or rods cumbersome to install and unsightly to consumers, and if damaged could lead to potential system communication problems.

The panel supervises every device (excluding the remote keyfob) to monitor current open/close state, tamper condition, serial number, date of manufacture, firmware revision, and battery status.

- > Access codes : 20 maximum, 4 - 6 digits; one installer access code for on-site programming only.
- > Configuration/Programming : on-site using alphanumeric keypads.
- > Communication : reports to central monitoring stations using Frontel.
- > Video verification : video resolution of 320 x 240 pixels, 0 lux sensitivity, 5-frames per second for approx. 10 seconds total recording time. 220K MPEG file.
- > History/Event Log : maximum 4,000 events stored in flash memory that cannot be cleared or erased.

Configuration/Programming

Complete system configuration/programming can be done on-site using alphanumeric keypads. Easy to understand text on a two line, 16-character liquid-crystal (LCD) display guides you through programming, prompting you for simple yes/no or data entry responses. Complete punctuation symbols allow for accurate website/IP address entries and device location naming.

Communication

The XL reports alarms and other system events by using the Frontel protocol. Frontel provides complete system reporting information and video verification to a central monitoring station set up with the Frontel alarm receiving software.

Voice Verification

The panel incorporates a speaker and a microphone. When using a GSM/GPRS simcard, the XL panel allows the monitoring station to do 2-way voice verification.

2-way voice can be launched at any time when the panel is connected to the monitoring station. During the 2 way voice, data connection and video download is suspended and resumes after the voice communication terminates.

Video Verification

Incorporating MotionViewer™ into the security system allows for video verification of intrusion alarms.

When the system is armed and an intruder trips MotionViewer™, the integrated camera captures a 10-second digital video clip which is sent to the central monitoring station by the control panel, which can forward them to an alert list.

History/Event Log

The XL GPRS control panel records and stores all system activities and events (armings, disarmings, alarms, access codes entered, system programming changes, etc.) in flash memory, that cannot be cleared or erased.

The log accumulates a maximum of 4,000 events. As additional events occur, the control panel automatically deletes the oldest event. This ensures the most recent events reside in the log.

The history/event log can be viewed using an alphanumeric keypad or downloaded at the monitoring station.

Compatibility

The XL series panel is compatible with all the Videofied® wireless devices described in this page:



Indoor MotionViewer™:

Integrated PIR motion detector, night vision digital camera, infrared illuminators.

The Indoor MotionViewer detect intruders and capture a video of the intrusion which is sent to the panel over RF.



Outdoor Badge Reader with Prox-Tag:

Allowing Arming/disarming of the system from outside the premises.

The Prox-Tags are standard Mifare badges.



Door Contact :

Detect door and window open/close activity.



Outdoor MotionViewer™:

Integrated PIR motion detector, night vision digital camera, infrared illuminators.

The Outdoor MotionViewer detect intruders and capture a video of the intrusion which is sent to the panel over RF.



Indoor Siren:

Provide status beeps and alarm sounds throughout the premises where needed.



Outdoor Siren/Strobe:

Provide alarm sounds and visual identification of alarm site for responding authorities.



Smoke Sensor:

Enhances protection and uses advanced smoke detection technology. Totally wireless and integrated to the security system.



Remote Keyfob:

Allow limited system operation and panic alarm capability in a portable, convenient package.

Security notes / (FR) Notes de sécurité / (DE) Hinweise zur Sicherheit

English

- Remove battery before any maintenance!
- **WARNING**, there is a risk of explosion if a battery is replaced by an incorrect type!
- Observe polarity when setting up the batteries!
- Do not throw used batteries! Bring them to your installer or a collection point.

Français

- Retirez les piles avant toute opération de maintenance!
- Attention ! Il y a un risque d'explosion si l'une des piles utilisées est remplacée par une pile de type incorrect!
- Respectez la polarité lors de la mise en place des piles!
- Ne jetez pas les piles usagées! Ramenez-les à votre installateur ou à un point de collecte spécialisé.

Deutsch

- Batterien vor jeglichen Wartungsarbeiten entfernen!
- Vorsicht, es besteht Explosionsgefahr, wenn eine Batterie durch eine Batterie falschen Typs ersetzt wird!
- Achten Sie beim Einsetzen der Batterien auf die Polung!
- Entsorgen Sie Batterien nicht im normalen Haushaltsmüll! Bringen Sie Ihre verbrauchten Batterien zu den öffentlichen Sammelstellen.

FCC Regulatory Information for USA and CANADA

FCC Part 15.21 Changes or modifications made to this equipment not expressly approved by RSI Video Technologies may void the FCC authorization to operate this equipment.

FCC Part 15.105 Class B

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference

to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- > Reorient or relocate the receiving antenna.
- > Increase the separation between the equipment and receiver.
- > Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- > Consult the dealer or an experienced radio/TV technician for help.

Radio frequency radiation exposure information according 2.1091 / 2.1093 / OET bulletin 65

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This device complies with Part 15 of the FCC Rules and with RSS-210 of Industry Canada.

Operation is subject to the following two conditions:

- 1 This device may not cause harmful interference, and
- 2 This device must accept any interference received, including interference that may cause undesired operation.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence.

L'exploitation est autorisée aux deux conditions suivantes:

- 1 L'appareil ne doit pas produire de brouillage, et
- 2 L'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

Operating Frequency	868/915/920 MHz
Required Voltage	Nominal voltage = 6 V Low battery limit = 4.2 V
Powering	Type B : 1 external power supply with battery backup 4x 1.5 Alkaline D cells (Option 1) or Type C: 8x 1,5 V D Alkaline batteries (Option 2)
Current consumption	Standby (1h average) = 420 µA ; Max = 1,3 A
Operating temperature	-10° / +40° C (-14° /+104° F)
Maximum relative humidity	75%, without condensing
Dimensions (LxWxD)	225 mm x 180 mm x 55 mm (9 in. x 7 in. x 2-1/6 in)
Weight	520 g (without batteries)

Approvals



EN50131-1: 2006; + A1: 2009	Grade 2 - Class II
<i>The panel must be used with a EN50131-3 certified keypad (CMA, XMA or XMB)</i>	
EN50131-3: 2009	Grade 2 - ACE Type B
EN50131-4: 2009	Grade 2 - Siren type W
EN50131-5-3: 2005; + A1: 2009	Grade 2
EN50131-6: 2008	Grade 2 - Type C
EN50130-4: 1995; + A1: 1998; + A2: 2003	
EN50130-5: 1998	Class II

Embedded

- Touchpad
 - Minimum number of variations PIN = 1109814
 - Number of forbidden PIN codes = 186 (See page 15)
 - Number of invalid passcode entries before disabling = 5
 - Waiting for input code = 60 s
 - Blocking time after 5 attempts invalid = 90 s
 - Battery life support memory = nd (Using flash memory)
- Badge Reader
 - ISO/IEC 14443A
- Siren
 - 15 min maximum duration
 - Indoor use only
 - Can be self-powered
 - 105 dB (A) at 1 meter



EMEA SALES

23, avenue du Général Leclerc
92340 BOURG-LA-REINE
FRANCE
E-Mail : emesales@rsivideotech.com

North American Headquarters

1375 Willow Lake Blvd, Suite 103
Vadnais Heights, MN 55110
USA
E-Mail : usasales@rsivideotech.com

